j5create JCD381-N USB Type-C™ Dual HDMI Mini Dock-Ethernet/ USB 3.1 HUB / PD2.0

Brand: j5create Product code: JCD381-N

Product name : JCD381-N USB Type-C™ Dual HDMI Mini

Dock-Ethernet/ USB 3.1 HUB / PD2.0



JCD381 USB Type-C Dual HDMI Mini Dock-Ethernet/ USB 3.1 Hub / PD2.0, includes 2x HDMI ports and 3x USB ports, Metallic Champagne

j5create JCD381-N USB Type-C™ Dual HDMI Mini Dock-Ethernet/ USB 3.1 HUB / PD2.0:

The USB-C® Dual HDMI™ Mini Dock provides extra connectivity for your USB-C® computer, featuring data transfer, power delivery and video displays. Easily add two additional USB™ computer peripherals, two HDMI™ monitors, and a Gigabit Ethernet connection through your USB-C® port. When connected to a power source, the USB-C® input charging port allows you to continue charging your laptop or smartphone. Its compact and lightweight design, making it great for use on the go.



Host interface * USB 3.2 Gen 1 (3.1 Gen 1) Type-C 1 USB 3.2 Gen 1 (3.1 Gen 1) Type-C 3 3 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 3 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 4 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 5 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 5 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 5 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 6 Subs 3.2 Gen 1 (3.1 Gen 1) Type-C 6 Subs Power Delivery up to 60 W Subs Power Up to 60				
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity '	Ports & interfaces		Software	
USB Type-C DisplayPort Alternate Mode Mode Network Storage temperature (T-T) 10 - 65 °C Storage temperature (T-T) 10 - 65 °C Operating temperature (T-T) 10 - 65 °C Operating temperature (T-T) 10 - 65 °C Operating relative humidity (H-H) 0 - 85% Ethernet LAN (RJ-45) ports 1 10,100,1000 Mbit/s Ethernet LAN data rates 10,100,1000 Mbit/s Weight & dimensions Weight & dimensions Width 130 mm Number of displays supported 2 Depth 15 mm Maximum refresh rate 30 Hz Maximum refresh rate 30 Hz Maximum refresh rate 30 Hz Mounterfaces HDMI, PS/Z, USB 3.2 Gen 1 (3.1 Gen 1) Type-A Plug and Play X Quantity per pack 1pc(s) Housing material Aluminium Package weight 193 mm Accountry of origin 1aiwan Package depth 125 mm Package depth 125 mm Package depth 125 mm Package weight 194.5 g Input current 3 A Packaging content 194.5 g Input current 20 V Output voltage 20 V Output voltage 20 V Output voltage 20 V Output current 30 A S Output voltage 20 V Output current 30 A S Output voltage 20 V Output voltage 30 V Output current 30 A S Output voltage 30 V	Host interface * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity USB Power Delivery USB Power Delivery up to	3 1 ✓ 60 W	Mac operating systems supported	10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0
Network Storage temperature (T-T) 10 - 40 °C 10 - 65 °C CEthernet LAN (RJ-45) ports Ethernet LAN (RJ-45) ports Ethernet LAN data rates 10,100,1000 Mbit/s Storage relative humidity (H-H) Operating relative humidity (H-H) O - 85% Corage relative humide humidite humidite humidite humidite humidite humidite humidite	' ' '	_	Operational conditions	
Ethernet LAN (RJ-45) ports 1 10,100,1000 Mbit/s Storage relative humidity (H-H) 0 - 85% 0 - 8	Mode	×	Operating temperature (T-T)	0 - 40 °C
Ethernet LAN data rates 10,100,1000 Mbit/s Storage relative humidity (H-H) 0 - 85% Performance Width 130 mm Number of displays supported 2 Depth 15 mm Maximum refresh rate 30 Hz Height 54 mm Mouth 115.5 g Maximum refresh rate 8 Beige, White Weight 115.5 g HUMI, PS/Z, USB 3.2 Gen 1 (3.1 Gen 1) Type-A Quantity per pack 1 pc(s) Plug and Play Aluminium Package width 193 mm Power Power Power Package weight 125 mm Power Supply 2.25 W Quick start guide Nanual Young turnent 0.45 A Packaging content Nanual Young House 1 x JCD381 USB-C® Dual HDMI™ Software Windows operating systems supported Technical details Storage relative humidity (H-H) 0 - 85% Weight 4 dimensions Weight 4 dimensions Width 130 mm Poepth 15 mm Packaging data Quantity per pack 1 pc(s) Packaging data Quantity per pack 1 pc(s) Package depth 125 mm Package depth 22.5 mm Package weight 194.5 g Input current 3 A Packaging content Quick start guide Manual Young 1 x JCD381 USB-C® Dual HDMI™ Mini Dock, 1 x Quick Installation Guide Windows operating systems Supported Technical details	Network		Storage temperature (T-T)	-10 - 65 °C
Performance HD type	Ethernet LAN (RJ-45) ports	1	Operating relative humidity (H-H)	0 - 85%
HD type	Ethernet LAN data rates	10,100,1000 Mbit/s	Storage relative humidity (H-H)	0 - 85%
Number of displays supported Ak Oltra HD Depth Height Foduct colour * Beige, White HDMI, PS/2, USB 3.2 Gen 1 (3.1 Gen 1) Type-A Plug and Play Housing material Country of origin Taiwan Power Input current Power supply Output voltage Output voltage Output current Software Windows 10, Windows 11, Yes Peth Depth 15 mm Peth 15, 5 g Packaging data 1) 175, 9 Packaging data 1) 175, 9 Packaging data 1) 1 pc(s) Package width 193 mm Package depth 125 mm Package depth 22.5 mm Package height 22.5 mm Package weight 194.5 g Ix JCD381 USB-C® Dual HDMI™ Mini Dock, 1 x Quick Installation Guide Fechnical details	Performance		Weight & dimensions	
Input current 3 A Packaging content Quick start guide Output voltage Output current Output current Output current Software Windows operating systems supported Packaging content Packaging content Packaging content Manual 1 x JCD381 USB-C® Dual HDMI™ Mini Dock, 1 x Quick Installation Guide Technical details	HD type Number of displays supported Maximum refresh rate Product colour * Hub interfaces Plug and Play Housing material Country of origin Power	2 30 Hz Beige, White HDMI, PS/2, USB 3.2 Gen 1 (3.1 Gen 1) Type-A Aluminium	Depth Height Weight Packaging data Quantity per pack Package width Package depth Package height	15 mm 54 mm 115.5 g 1 pc(s) 193 mm 125 mm 22.5 mm
Power supply 2.25 W Output voltage 20 V Output current 0.45 A Software Windows operating systems supported 2.25 W Quick start guide Manual ✓ 1 x JCD381 USB-C® Dual HDMI™ Mini Dock, 1 x Quick Installation Guide Technical details	Input current		5 5	13 1.3 g
Output voltage Output current Output curren	Power supply			1
Output current 0.45 A 1 x JCD381 USB-C® Dual HDMI™ Software Packaging content Mini Dock, 1 x Quick Installation Guide Windows operating systems supported Windows 10, Windows 11, Yes Technical details	Output voltage		,	
Windows operating systems supported Windows 10, Windows 11, Yes Technical details	Software	0.45 A		Mini Dock, 1 x Quick Installation
	Windows operating systems supported	Windows 10, Windows 11, Yes	Technical details	
Warranty period 2 year(s)			Warranty period	2 year(s)

Other features

Cable length 0.2 m Maximum operating temperature 40 $^{\circ}\mathrm{C}$



4712795081831

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.