

## D-Link DES-105 Unmanaged L2 Black

Brand : D-Link

Product code: DES-105/E

Product name : DES-105



5x 10/100 Mbps LAN, 1 Gbps, 2K MAC

D-Link DES-105. Switch type: Unmanaged, Switch layer: L2. Basic switching RJ-45 Ethernet ports quantity: 5. Full duplex. MAC address table: 2000 entries, Switching capacity: 1 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack

Management features		Technical details	
Switch type *	Unmanaged	Shipping (inner) case net weight	4.5 kg
Switch layer	L2	Products per shipping (inner) case	10 pc(s)
Quality of Service (QoS) support	✓	Pallet gross weight (air)	434 kg
Ports & interfaces		Master (outer) cases per pallet (air)	75 pc(s)
Basic switching RJ-45 Ethernet ports quantity *	5	Products per pallet (air)	750 pc(s)
Power connector	DC-in jack	Pallet gross length	120 cm
Network		Pallet gross width	110 cm
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Pallet height (air)	2.04 m
10G support *	✗	Pallet gross weight (sea)	434 kg
Copper ethernet cabling technology	100BASE-TX, 10BASE-T	Master (outer) cases per pallet (sea)	75 pc(s)
Full duplex	✓	Products per pallet (sea)	750 pc(s)
Flow control support	✓	Pallet height (sea)	2.04 m
Auto MDI/MDI-X	✓	Shipping (inner) case gross weight	5.5 kg
Data transmission		Power	
Supported data transfer rates	10/100 Mbps	Input current	1 A
Switching capacity *	1 Gbit/s	Input voltage	5 V
MAC address table *	2000 entries	Power consumption (typical)	1.9 W
Store-and-forward	✓	Power over Ethernet (PoE)	
Maximum data transfer rate	0.1 Gbit/s	Power over Ethernet (PoE) *	✗
Jumbo frames support	✓	Operational conditions	
Packet buffer memory	0.384 MB	Operating temperature (T-T)	0 - 50 °C
Security		Storage temperature (T-T)	-10 - 70 °C
MAC address filtering	✓	Operating relative humidity (H-H)	10 - 90%
Design		Storage relative humidity (H-H)	5 - 90%
Rack mounting *	✗	Weight & dimensions	
Product colour	Black	Weight	265 g
Housing material	Metal	Packaging data	
LED indicators	Link, Power	Package width	170 mm
Certification	RoHS, FCC Class B, ICES-003 Class B, CE Class B, C-Tick Class B, VCCI Class B, cUL, CB	Package depth	220 mm
Performance		Package height	62 mm
Mean time between failures (MTBF)	495709 h	Package weight	450 g
Technical details		Logistics data	
Shipping (inner) case height	36.6 cm	Harmonized System (HS) code	85176990
Shipping (inner) case width	23 cm	Other features	
Shipping (inner) case length	33.5 cm	Data transfer rate	200 Mbit/s
		Dimensions (WxDxH)	100 x 98 x 28 mm
		Connectivity technology	Wired



0790069368189



790069368189



4055895266532

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.