



## APC SMC1000IC uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W 8 AC outlet(s)

**Brand :** APC

**Product code:** SMC1000IC

**Product name :** SMC1000IC

1 kVA, 600W, 170-300V, 50/60Hz, 455J, 171x439x219mm, 17.27kg, Black  
APC SMC1000IC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 600 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery life (max): 5 year(s), Battery recharge time: 3 h. Form factor: Mini Tower, Product colour: Black, Display type: LCD. Width: 171 mm, Depth: 439 mm, Height: 219 mm




Features		Battery	
UPS topology *	Line-Interactive	Battery life (max)	5 year(s)
Output power capacity *	1 kVA	Battery recharge time	3 h
Output power *	600 W	Hot-swap battery	✓
Waveform *	Sine	Automatic battery test	✓
Input operation voltage (min) *	170 V	Cold start	✓
Input operation voltage (max) *	300 V	<b>Design</b>	
Input frequency *	50/60 Hz	Form factor *	Mini Tower
Output operation voltage (min)	220 V	Product colour *	Black
Output operation voltage (max)	240 V	Display type	LCD
Output frequency	50/60 Hz	LED indicators	✓
Automatic Voltage Regulation (AVR)	✓	Certification	CE, CSA, GOST, UL 1778, VDE
Surge energy rating	455 J	<b>Operational conditions</b>	
Output voltage Total Harmonic Distortion (THD)	5%	Operating temperature (T-T)	0 - 40 °C
Noise level	41 dB	Storage temperature (T-T)	-15 - 45 °C
Surge protection	✓	Operating relative humidity (H-H)	0 - 95%
Audible alarm(s)	✓	Storage relative humidity (H-H)	0 - 95%
Web-based management	✓	Operating altitude	0 - 3000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Non-operating altitude	0 - 15000 m
Auto-restart	✓	<b>Technical details</b>	
Temperature voltage compensation	✓	Sustainability certificates	Green Premium
Ports & interfaces		Weight & dimensions	
AC outlet types	C13 coupler	Width	171 mm
Power plug	C14 coupler	Depth	439 mm
AC outlets quantity	8 AC outlet(s)	Height	219 mm
USB port	✓	Weight	17.3 kg
USB 2.0 ports quantity	1	Package width	328 mm
Serial ports quantity	1	Package depth	595 mm
Ethernet LAN (RJ-45) ports	1	Package height	376 mm

Battery		Weight & dimensions	
Battery technology	Sealed Lead Acid (VRLA)	Package weight	19.6 kg
		Packaging data	
		Cables included	USB cable
		Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	18 pc(s)
		Harmonized System (HS) code	85078000



0731304332947



731304332947

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 01-JUL-2024. Prints or copies of Information are only valid on the printed Publication date