Epson LQ-590II dot matrix printer 550 cps

Brand : Epson **Product code:** C11CF39403

Product name: LQ-590II

Impact Dot Matrix, 24pins, 80colums, 24 Needles, 550cps, USB 2.0, 55dB, 128kB

Epson LQ-590II dot matrix printer 550 cps:


The LQ-590II is a high-volume dot matrix printer designed for fast and reliable printing. Upgrade your existing dot matrix printers to our latest model, which is now Energy Star compliant, and delivers an incredibly low TCO.

Epson LQ-590II. Maximum print speed: 550 cps, Built-in barcodes: Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E, Character sets: ISO 8859-15, Italic, PC437, PC850, PC858, Roman 8. Continuous paper thickness range: 0.065 - 0.49 mm. Product colour: Black, Buffer size: 128 KB, Sound pressure level (printing): 55 dB. Standard interfaces: USB 2.0. Print head: 24-pin, Print head life: 400000000 million characters, Mean time between failures (MTBF): 25000 h





Printing		Weight & dimensions	
Maximum printing width (columns) *	80	Width	437 mm
Maximum print speed *	550 cps	Depth	375 mm
Built-in barcodes	Code 39, EAN13, EAN8, Interleaved 2/5, POSTNET, UPC-A, UPC-E ISO 8859-15, Italic, PC437, PC850, PC858, Roman 8	Height Weight	177 mm 7.2 kg
Character sets		Packaging data	
Paper handling		Quantity per pack	1 pc(s)
Continuous paper thickness range	0.065 - 0.49 mm	Package width Package depth	446 mm 534 mm
Features		Package height	281 mm
Product colour *	Black	Package weight	8.91 kg
Buffer size *	128 KB 55 dB Indonesia	Technical details	
Sound pressure level (printing) * Country of origin		Sustainability certificates	ENERGY STAR
Ports & interfaces	maonesia	Logistics data	
Standard interfaces *	USB 2.0	Products per pallet	14 pc(s)
Endurance		Pallet gross length Pallet gross width	120 cm 80 cm
Print head *	24-pin	Pallet gross height	7.43 m
Print head life	40000000 million characters	Products per pallet layer	2 pc(s)
Mean time between failures (MTBF)	25000 h	Products per pallet layer (UK)	4 pc(s)
Operational conditions		Products per pallet (UK)	28 pc(s)
Operating temperature (T-T)	5 - 35 °C	Pallet length (UK)	120 cm
Operating relative humidity (H-H)	10 - 80%	Pallet width (UK)	100 cm
		Pallet height (UK)	7.43 m



8715946649863

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.