



## APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

Brand : APC

Product code: SMT750IC

Product name : APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA

APC Smart-UPS SMT750IC - 6x C13, USB, SmartConnect, 750VA. UPS topology: Line-Interactive, Output power capacity: 0.75 kVA, Output power: 500 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 4.6 min, Typical backup time at half load: 15.8 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Width: 138 mm, Depth: 358 mm, Height: 157 mm




| Features                             |                         | Battery                           |   |
|--------------------------------------|-------------------------|-----------------------------------|---|
| UPS topology *                       | Line-Interactive        | Cold start                        | ✓   |
| Output power capacity *              | 0.75 kVA                | <b>Design</b>                     |   |
| Output power *                       | 500 W                   | Form factor *                     | Tower   |
| Waveform *                           | Sine                    | Cable length                      | 1.83 m  |
| Input operation voltage (min) *      | 151 V                   | Product colour *                  | Black   |
| Input operation voltage (max) *      | 302 V                   | Display type                      | LCD   |
| Input frequency *                    | 50/60 Hz                | LED indicators                    | Status  |
| Output operation voltage (min)       | 220 V                   | Certification                     | CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, UL 1778, VDE, REACH, PEP, EOLI |
| Output operation voltage (max)       | 240 V                   | <b>Operational conditions</b>     |   |
| Automatic Voltage Regulation (AVR) ✓ |                         | Operating temperature (T-T)       | 0 - 40 °C   |
| Surge energy rating                  | 540 J                   | Storage temperature (T-T)         | -15 - 45 °C   |
| Efficiency                           | 98%                     | Operating relative humidity (H-H) | 5 - 95%   |
| Noise level                          | 40 dB                   | Storage relative humidity (H-H)   | 0 - 95%   |
| Audible alarm(s) ✓                   |                         | Operating altitude                | 0 - 3000 m  |
| Auto-restart ✓                       |                         | Non-operating altitude            | 0 - 15000 m   |
| <b>Ports &amp; interfaces</b>        |                         | <b>Technical details</b>          |   |
| AC outlet types                      | C13 coupler             | Sustainability certificates       | Green Premium   |
| Power plug                           | C14 coupler             | Compliance certificates           | RoHS  |
| AC outlets quantity                  | 6 AC outlet(s)          | <b>Weight &amp; dimensions</b>    |   |
| Number of output IEC jumpers         | 2                       | Width                             | 138 mm  |
| USB port ✓                           |                         | Depth                             | 358 mm  |
| Ethernet LAN (RJ-45) ports           | 1                       | Height                            | 157 mm  |
| SmartSlot ✓                          |                         | Weight                            | 13.2 kg   |
| <b>Battery</b>                       |                         | Package width                     | 278 mm  |
| Battery technology                   | Sealed Lead Acid (VRLA) | Package depth                     | 499 mm  |
| Typical backup time at full load     | 4.6 min                 | Package height                    | 301 mm  |
| Typical backup time at half load     | 15.8 min                |                                   |   |
| Battery life (max)                   | 5 year(s)               |                                   |   |

| Battery                |     | Weight & dimensions         |                           |
|------------------------|-----|-----------------------------|---------------------------|
| Battery recharge time  | 3 h | Package weight              | 14.2 kg                   |
| Hot-swap battery       | ✓   | <b>Packaging data</b>       |                           |
| Automatic battery test | ✓   | Cables included             | USB cable                 |
|                        |     | Manual                      | ✓                         |
|                        |     | Quick installation guide    | ✓                         |
|                        |     | Bundled software            | Powershute Serial Edition |
|                        |     | <b>Logistics data</b>       |                           |
|                        |     | Products per pallet         | 24 pc(s)                  |
|                        |     | Harmonized System (HS) code | 85078000                  |



0731304340317



731304340317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.