StarTech.com VGA to RCA and S-Video Converter - USB Power

Brand : StarTech.com Product code: VGA2VID2

Product name : VGA to RCA and S-Video Converter - USB

Power

- Provides output in both Composite and S-Video formats
- Supports PC input resolutions up to 1920 x 1080
- Select between NTSC and PAL outputs
- Dynamically adjust image underscan and overscan
- Powered by USB port

 $Star Tech.com\ 1080p\ VGA\ to\ RCA\ Converter\ -\ PC\ to\ TV\ -\ USB\ Powered\ S-Video\ Converter\ with\ Dynamic\ Scaling\ (VGA2VID2)$

StarTech.com VGA to RCA and S-Video Converter - USB Power. Converter type: Active video converter, Product colour: Black, Certification: CE, FCC, REACH. Maximum video resolution: 1920 x 1080 pixels, Video resolutions: 640 x 480,1920 x 1080 pixels, Maximum refresh rate: 60 Hz. Host interface: VGA (D-Sub), Output interface: Composite/S-Video. Power consumption (typical): 2.5 W. Width: 54 mm, Depth: 60 mm, Height: 20 mm







| Features | | Operational conditions | |
|---|---|-----------------------------------|-----------|
| Converter type * Product colour Certification | Active video converter Black CE, FCC, REACH | Operating relative humidity (H-H) | 5 - 90% |
| | | Weight & dimensions | |
| | | Width | 54 mm |
| Video | | Depth | 60 mm |
| Maximum video resolution * | 1920 x 1080 pixels | Height | 20 mm |
| Video resolutions | 640 x 480,1920 x 1080 pixels | Weight | 46 g |
| Maximum refresh rate | 60 Hz | Packaging data | |
| Ports & interfaces | | Cables included | USB |
| Host interface * | VGA (D-Sub) | Quick installation guide | ✓ |
| Output interface * | Composite/S-Video | Quantity | 1 |
| Power | | Package width | 133 mm |
| USB powered | 1 | Package depth | 105 mm |
| Power consumption (typical) | 2.5 W | Package height | 24 mm |
| Technical details | | Package weight | 162 g |
| Sustainability certificates | RoHS | Logistics data | |
| Compliance certificates | RoHS | Harmonized System (HS) code | 85176990 |
| · | Tion 15 | Master (outer) case width | 540 mm |
| Operational conditions | | Master (outer) case length | 568 mm |
| Operating temperature (T-T) | 0 - 50 °C | Master (outer) case height | 351 mm |
| Storage temperature (T-T) | -10 - 80 °C | Products per master (outer) case | 100 pc(s) |





065030882590

0065030882590

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.