Intellinet 8-Port Gigabit Ethernet PoE+ Switch, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 60 W, Desktop (UK power cord)

Brand : Intellinet

Product name : 8-Port Gigabit Ethernet PoE+ Switch, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 60 W, Desktop (UK power cord)

Product code: 561204-UK

8-Port Gigabit Ethernet PoE+ Switch, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 60 W, Desktop (UK 3-pin plug)
Intellinet 8-Port Gigabit Ethernet PoE+ Switch, IEEE 802.3at/af Power over Ethernet (PoE+/PoE) Compliant, 60 W, Desktop (UK power cord). Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8. Full duplex. MAC address table: 4096 entries, Switching capacity: 16 Gbit/s. Networking standards: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power over Ethernet (PoE)

Ports & interfaces

Basic switching RJ-45 Ethernet ports quantity *	8
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)

Network

Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x
Copper ethernet cabling technology	10BASE-T, 100BASE-TX, 1000BASE-T
Full duplex	✔
Flow control support	✔
Auto MDI/MDI-X	✔
Auto-sensing	✔
VLAN support	✔
Virtual LAN features	Private VLAN

Data transmission

Switching capacity *	16 Gbit/s
MAC address table *	4096 entries
Store-and-forward	✔
Packet forwarding rate (1 Gbps)	1488000 pps
Packet forwarding rate (100 Mbps)	148800 pps
Packet forwarding rate (10 Mbps)	14880 pps

Design

Rack mounting *	✘
Product colour	Black

Design

Housing material	Metal
LED indicators	Activity, Link, PoE, Power
Certification	FCC Class B, CE, RoHS

Power

Power supply included *	✔
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Power consumption (max)	67.3 W

Power over Ethernet (PoE)

Power over Ethernet (PoE) *	✔
Power over Ethernet (PoE) type supported	PoE+
Total Power over Ethernet (PoE) budget	60 W

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Operating relative humidity (H-H)	10 - 90%

Weight & dimensions

Width	155 mm
Depth	118 mm
Height	46 mm
Weight	930 g

Packaging data

Cables included	AC
Manual	✔
Package type	Box

0766623995719

766623995719