

## DeepCool PQ850 power supply unit 850 W 20+4 pin ATX ATX Black

**Brand :** DeepCool

**Product code:** R-PQ850M-FA0B-UK

**Product name :** PQ850

PQ850M, 120mm FDB, Hybrid Fanless Mode, 80 PLUS Gold, Modular, UK Plug  
 DeepCool PQ850. Total power: 850 W, AC input voltage: 100 - 240 V, AC input frequency: 50 - 60 Hz.  
 Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 61 cm, SATA power cable length: 450 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX, 80 PLUS certification: 80 PLUS Gold. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Cables included: AC, CPU, PCIe, Peripheral (Molex), SATA



Power		Ports & interfaces	
Total power *	850 W	CPU power connector (4+4 pin)	✓
AC input voltage *	100 - 240 V	CPU power cable length	65 cm
AC input frequency	50 - 60 Hz	ATX power connector (20+4 pin)	✓
Input current	12 - 6 A	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	100 W	Performance	
Combined power (+12V)	840 W	80 PLUS certification *	80 PLUS Gold
Combined power (+5V)	100 W	Supported motherboard form factors	ATX
Combined power (-12V)	3.6 W	Purpose *	PC
Combined power (+5Vsb)	15 W	Power supply unit (PSU) form factor *	ATX
Max output current (+3.3V)	20 A	ATX version	2.4
Max output current (+12V)	70 A	Silent mode	✓
Max output current (+5V)	20 A	Bearing technology	FDB
Max output current (-12V)	0.3 A	Mean time between failures (MTBF)	100000 h
Max output current (+5Vsb)	3 A	Design	
Hold time	16 ms	Product colour	Black
Efficiency	90%	Cooling type	Active
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	Fan diameter	12 cm
		Number of fans	1 fan(s)
		Fan location	Top
		On/off switch	✓
Ports & interfaces		Operational conditions	
Motherboard power connector *	20+4 pin ATX	Operating temperature (T-T)	0 - 50 °C
Motherboard power cable length	61 cm	Packaging content	
Number of SATA power connectors	8	Cables included	AC, CPU, PCIe, Peripheral (Molex), SATA
SATA power cable length	450 mm	Cable tie(s) included	✓
Peripheral (Molex) power connectors (4-pin) *	5	Weight & dimensions	
Peripheral (Molex) power cable length	450 mm	Width	150 mm
PCI Express power connectors (6+2 pin)	3	Depth	140 mm
PCI Express power cable length	75 cm	Height	86 mm
CPU P4 connector (4-pin)	2	Technical details	
		Sustainability certificates	ErP

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.