



APC SMT3000IC uninterruptible power supply (UPS) Line-Interactive 3 kVA 2700 W 9 AC outlet(s)

Brand : APC

Product code: SMT3000IC

Product name : SMT3000IC

- Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices

- Includes: CD with software, Documentation CD, USB cable

2.7 kW, 3 kVA, 230V, 1x IEC 320 C19, 1x IEC Jumpers, 8x IEC 320 C13, SmartSlot, USB, 365 Joules
APC SMT3000IC. UPS topology: Line-Interactive, Output power capacity: 3 kVA, Output power: 2700 W.
AC outlet types: C13 coupler, C19 coupler, Power plug: C20 coupler, AC outlets quantity: 9 AC outlet(s).
Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 5.1 min, Typical backup time at half load: 17.2 min. Form factor: Tower, Product colour: Black, Cable length: 1.83 m. Width: 197 mm, Depth: 544 mm, Height: 435 mm



Features		Battery	
UPS topology *	Line-Interactive	Hot-swap battery	✓
Output power capacity *	3 kVA	Automatic battery test	✓
Output power *	2700 W	Cold start	✓
Waveform *	Sine		
Input operation voltage (min) *	151 V		
Input operation voltage (max) *	302 V		
Input frequency *	50/60 Hz		
Output operation voltage (min)	220 V		
Output operation voltage (max)	240 V		
Output frequency	50/60 Hz		
Automatic Voltage Regulation (AVR)	✓		
Surge energy rating	365 J		
Efficiency	98.4%		
Emergency Power Off (EPO)	✓		
Noise level	53 dB		
Audible alarm(s)	✓		
Auto-restart	✓		
Ports & interfaces		Design	
AC outlet types	C13 coupler, C19 coupler	Form factor *	Tower
Power plug	C20 coupler	Cable length	1.83 m
AC outlets quantity	9 AC outlet(s)	Product colour *	Black
Number of output IEC jumpers	2	Display type	LCD
USB port	✓	LED indicators	Status
SmartSlot	✓	Certification	CE, CSA, EAC, EN/IEC 62040-1, EN/IEC 62040-2, RCM, VDE, REACH, PEP, EOL1
Battery		Operational conditions	
Battery technology	Sealed Lead Acid (VRLA)	Operating temperature (T-T)	0 - 40 °C
Typical backup time at full load	5.1 min	Storage temperature (T-T)	-15 - 45 °C
Typical backup time at half load	17.2 min	Operating relative humidity (H-H)	0 - 95%
		Storage relative humidity (H-H)	0 - 95%
		Operating altitude	0 - 3000 m
		Non-operating altitude	0 - 15000 m
		Technical details	
		Sustainability certificates	Green Premium
		Compliance certificates	RoHS
		Weight & dimensions	
		Width	197 mm
		Depth	544 mm
		Height	435 mm
		Weight	52.5 kg
		Package width	381 mm

Battery		Weight & dimensions	
Battery life (max)	5 year(s)	Package depth	762 mm
Battery recharge time	3 h	Package height	699 mm
		Package weight	63.7 kg
Packaging data			
		Cables included	RS-232, USB cable
		Quick installation guide	✓
Logistics data			
		Products per pallet	9 pc(s)
		Harmonized System (HS) code	85078000



0731304337331



731304337331



5706998577092

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.