

Samsung QET 55" Crystal UHD 4K Signage QE55T

Brand : Samsung

Product family: QET

Product code:
LH55QETELGCXEN

Product name : 55" Crystal UHD 4K Signage QE55T



- Upscale your business
- Incredible UHD picture quality
- Crisp and vivid color expression

55", LED, 4K UHD (3840 x 2160), 300 nit, 4000:1, 89/89, 6.5 ms, RJ-45, HDCP, HDMI, RS232, AC 100-240V, 50/60Hz, 1230.5 x 707.2 x 59.9 mm, 14.1 kg

Samsung QET 55" Crystal UHD 4K Signage QE55T. Product design: Digital signage flat panel. Display diagonal: 139.7 cm (55"), Display resolution: 3840 x 2160 pixels, Display brightness: 300 cd/m², HD type: 4K Ultra HD. Operating system installed: Tizen 4.0. Product colour: Black



Display		Design	
LED backlight	✓	Panel mounting interface	200 x 200 mm
Display diagonal *	139.7 cm (55")	Bezel colour	Black
Display resolution *	3840 x 2160 pixels	Performance	
Display brightness *	300 cd/m ²	Purpose *	Commercial
HD type *	4K Ultra HD	HDCP	✓
Touchscreen *	✗	HDCP version	2.2
Response time	6.5 ms	Power	
Contrast ratio (typical)	4000:1	Power consumption (typical) *	154 W
Dynamic contrast ratio marketing name	Mega DCR	Power consumption (sleep)	0.5 W
Viewing angle, horizontal	89°	Energy efficiency class (SDR)	G
Viewing angle, vertical	89°	Energy consumption (SDR) per 1000 hours	105 kWh
Pixel pitch	0.105 x 0.315 mm	AC input voltage	100 - 240 V
Display diagonal (metric)	138 cm	AC input frequency	50/60 Hz
Horizontal scan range	15 - 135 kHz	Energy efficiency scale	A to G
Vertical scan range	24 - 75 Hz	Computer system	
Haze rate	2%	Operating system installed	Tizen 4.0
Pixel frequency (max)	594 MHz	Weight & dimensions	
Colour gamut	72%	Display width	1230.5 mm
Ports & interfaces		Display depth	59.9 mm
HDMI ports quantity *	2	Display height	707.2 mm
HDMI version	2.0	Display weight	14.1 kg
HDMI input ports quantity	2	Packaging data	
DVI port *	✗	Package width	1386 mm
USB port *	✓	Package depth	158 mm
USB ports quantity	1	Package height	843 mm
Ethernet LAN *	✓	Package weight	20.2 kg
Wi-Fi *	✗	Operational conditions	
Audio (L/R) out	1	Operating temperature (T-T)	0 - 40 °C
RS-232 interface	✓	Operating relative humidity (H-H)	10 - 80%
Design		Certificates	
Product design *	Digital signage flat panel	Certification	Class B 60950-1
Placement supported *	Indoor		
Product colour *	Black		
Screen shape	Flat		

Design

VESA mounting *

**Other features**

Flash memory

8000 MB

Optional features

WMN4070SE STN-L4355F



8806090505195

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-JUL-2024. Prints or copies of Information are only valid on the printed Publication date