## **ZYXEL**

# **Zyxel POE12-60W 5 Gigabit Ethernet**

**Brand :** Zyxel **Product code:** POE12-60W-GB0101F

**Product name:** POE12-60W

- MultiGig tot 5G PoE++ Injector
- 60W PoE++ / UPoE 802.3af/at en 802.3bt standaard
- Single port Powerinjector
- Eenvoudige installatie voor IEEE 802.3bt compatibele draadloze LAN Aps, IP-videocamera's of IP-telefoons

Single 1-2.5-5G MultiGig 802.3bt PoE++ Injector [POE12-60W], GB

## Zyxel POE12-60W 5 Gigabit Ethernet:

### Support 5G Blazing-fast Network Speed

PoE12-60W is a Multi-Gigabit PoE injector supporting network speeds of up to 5Gbps. It is allowed to connect powered devices through existing Cat 5e or above cable.

#### **High PoE Power**

PoE12-60W complies with PoE++ providing PoE power up to 60 watts. It offers interoperability and compatibility with other standard-based PoE devices.

#### Plug and Play—Ease of Use

PoE12-60W is easy to connect network devices without any configuration. The wall-mount and desktop design accommodate most installations scenarios.





Network		Operational conditions	
Ethernet interface type Ethernet LAN data rates Power over Ethernet (PoE)	5 Gigabit Ethernet 10,100,1000,2500,5000 Mbit/s ✓	Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	5 - 90% -25 - 65 °C 5 - 90%
Networking standards	IEEE 802.3ab, IEEE 802.3bt, IEEE 802.3bz, IEEE 802.3u	Weight & dimensions	
Features	·	Width Depth	140 mm 65 mm
Product colour LED indicators	Black  China	Height Weight	38.5 mm 278 g
Country of origin  Ports & interfaces	China	Packaging data	
Ethernet LAN (RJ-45) ports RJ-45 input ports RJ-45 output ports	2 1 1	Package width Package depth Package height Package weight	168 mm 142 mm 47 mm 1.12 kg
Power		Packaging content	
AC adapter input voltage AC adapter frequency Total Power over Ethernet (PoE)	100-240 V 50/60 Hz	Number of products included Power cord included	1 pc(s) ✓
budget	60 W	Logistics data	85044095
Operational conditions Operating temperature (T-T) Operating temperature (T-T)	-10 - 40 °C 14 - 104 °F	Harmonized System (HS) code	65044095



4718937621675

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.