Epson SureColor SC-T5100N large format printer Wi-Fi Inkjet Colour 2400 x 1200 DPI A1 (594 x 841 mm) Ethernet LAN

Brand : Epson

Product family: SureColor

Product code: C11CF12302A1

Product name : SC-T5100N

- Flexibility: Available as a desktop version (no stand)

- Clean design: Thoughtfully designed to fit seamlessly into most environments

- Ease of use: Even when away from the desktop

- Peace of Mind: Unique Nozzle Verification Technology (NVT) helps prevent misprints

A1, 50ml ink tank, 2400 x 1200 DPI, USB 3.0, Gigabit Ethernet, Wi-Fi 802.11 b/g/n Epson SureColor SC-T5100N. Print technology: Inkjet, Maximum resolution: 2400 x 1200 DPI, Page description languages: ESC/P-R, HP-GL/2, HP-RTL. Maximum print size: A1 (594 x 841 mm), ISO A-series sizes (A0...A9): A1, A2, A3, A3+, A4, ISO B-series sizes (B0...B9): B1, B2, B3, B4, B5. Ethernet interface type: Gigabit Ethernet, USB connector: USB Type-A, Ethernet LAN data rates: 10,100,1000 Mbit/s. Display: LCD, Display diagonal: 10.9 cm (4.3"), Control type: Touch. Power consumption (standby): 8 W, Power consumption (typical): 28 W, Power consumption (off): 0.2 W

PrintingPerformancePrint technology*InkjetSound pressure level (printing)49 dBColour*✓RAM capacity1 GBMaximum resolution*2400 x 1200 DPICourty of originIndonesiaPage description languages*ESC/P-R, HP-GL/2, HP-RTLPowerPowerPrinting colours*Black, Cyan, Magenta, YellowPower consumption (standby)8 WPaper handlingPower consumption (typical)28 WMaximum print size*A1 (594 x 841 mm)Power consumption (off)0.2 WISO A-series sizes (AOA9)B1, B2, B3, B4, B5Windows operating systems supported✓Nedia thickness0.05 - 0.27 mmWindows operating systems supported✓Roll paper✓Width1268 mmPotrs & interfacesGigabit EthernetDepth505 mmWi-Fi*✓Width1268 mmUSB port*VVeright33 kgUSB connectorUSB Type-APackage depth530 mmUSB 2-Gen 1 (3.1 Gen 1) ports1Package weight45.5 kgSulti-In display*✓Package weight45.5 kgBuilt-In display*✓Package weight45.5 kgDisplay diagonalLOPTorride(s) included✓Display diagonalLOPTorride(s) included✓Display diagonal10.9 cm (4.3*)Country certrade serverFackager weight4.5 kgCounty torpeTouchTouchCountry certrade serverFackager weight4.5 k				
Colour *RAM capacity1 GBMaximum resolution *2400 x 1200 DPICountry of originIndonesiaPage description languages *ESC/PR, HP-GL2, HP-RTL Black, Cyan, Magenta, YellowPowerPowerPaper handlingPower consumption (standby)8 WMaximum print size *A1 (594 x 841 mm)Power consumption (oft)28 WISO A series sizes (A0A9)A1, A2, A3, A3+, A4Sumer equirementsSUMEISO A series sizes (B0B9)B1, B2, B3, B4, B5Windows operating systems supportedMedia thickness0.05 - 0.27 mmWindows operating systems supportedRoll paperWight & dimensionsWi-Fi*Wight2268 mmButterfaces typeGigabit EthernetDepthS05 mmEthernet LAN*200 mmUSB port*Suger data230 mmUSB scenctorUSB Type-APackage depth530 mmUSB scenctorUSB Type-APackage depth530 mmUSB scenctorUSB Type-APackage depth530 mmUSB scenctorUSB Type-APackage depth530 mmPerformancePackage weight45.5 kgBuilt-in display*CDAnualUsplay diagonal10.9 cm (4.3")Cutridge(s) includedDisplay diagonal10.9 cm (4.3")Cutridge(s) includedDisplay diagonal10.9 cm (4.3")Cutridge(s) includedOutro TypeTouch<	Printing		Performance	
Printing colours* Black, Cyan, Magenta, Yellow Power consumption (standby) 8 W Paper handling Power consumption (typical) 28 W Maximum print size* A1 (594 x 841 mm) Power consumption (off) 0.2 W ISO A-series sizes (AOA9) A1, A2, A3, A3+, A4 System requirements Vertice ISO B-series sizes (BOB9) B1, B2, B3, B4, B5 Windows operating systems supported Image and the system supported Image and the system supported Roll paper Image and the system supported Wi-Fi* Image and the system supported Wi-Fi* Image and the system supported Wi-Fi* Image and the system supported Wi-Fi* Image and the system supported	Colour *	4	RAM capacity	1 GB
Paper handlingPower consumption (typical)28 WMaximum print size*A1 (594 x 841 mm)Power consumption (off)0.2 WISO A-series sizes (A0A9)A1, A2, A3, A3+, A4System requirementsSystem requirementsISO B-series sizes (B0B9)B1, B2, B3, B4, B5Windows operating systems supportedImage: Construct of the system supportedImage: Construct of the system supportedMedia thickness0.05 - 0.27 mmWindows operating systems supportedImage: Construct of the system supportedImage: Construct of the system supportedMol paper0.05 - 0.27 mmWindows operating systems supportedImage: Construct of the system supportedImage: Construct of the system supportedPorts 6 interfaces0.05 - 0.27 mmWindows operating systems supportedImage: Construct of the system supportedWi-Fi*Image: Construct of the system system supportedImage: Construct of the system syst				9 W
Maximum print size*A1 (594 x 841 mm)Power consumption (off)0.2 WISO A-series sizes (A0A9)A1, A2, A3, A3+, A4System requirementsSystem requirementsISO B-series sizes (B0B9)B1, B2, B3, B4, B5Windows operating systemsImage: Additional systemsMedia thickness0.05 - 0.27 mmWindows operating systems supportedImage: Additional systemsRoll paperImage: Additional systemsImage: Additional systemsImage: Additional systemsWi-Fi*Image: Additional systemsImage: Additional systemsImage: Additional systemsUSB system * Image: Additional systemsImage: Additional systemsImage: Additional systemsUSB system * Image: Additional systemsImage: Additional systemsImage: Additional systemsUSB system * Image: Additional systemsImage: Additional systemsImage: Additional systemsUSB system * Image: Additional system * Image: Additional system * Image: Additional system * Image: Additional system * Image: Addi	Paper handling			
ISO B-series sizes (B0B9) B1, B2, B3, B4, B5 System requirements Media thickness 0.05 - 0.27 mm windows operating systems supported Roll paper Image: Ima	ISO A-series sizes (A0A9) ISO B-series sizes (B0B9) Media thickness	A1, A2, A3, A3+, A4 B1, B2, B3, B4, B5 0.05 - 0.27 mm		
Media thickness0.05 - 0.27 mmWindows operating systems supportedImage: Support of the systems support of the systems whether the systems the systems support of the systems support of the systems support of the systems support of the systems support of the systems 			System requirements	
Ports & interfaces Weight & dimensions Wi-Fi* ✓ Ethernet interface type Gigabit Ethernet Ethernet LAN* ✓ VSB port * ✓ VSB connector USB Type-A VSB 3.2 Gen 1 (3.1 Gen 1) ports 1 quantity 1 Ethernet LAN data rates 10.100.000 Mbit/s Performance Package weight Built-in display * ✓ Display diagonal 10.9 cm (4.3") Control type Touch Sound power level (standby) 32 dB			supported	-
Wi-Fi*Image: Constraint of the second se		v	1 3 3 11	4
Ethernet interface typeGigabit EthernetWith the fuel of			Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) ports quantity1Packaging dataEthernet LAN data rates10,100,000 Mbit/sPackage width730 mmPerformance10,100,000 Mbit/sPackage depth1530 mmPerformancePackage height655 mm655 mmBuilt-in display *Package weight45.5 kgDisplayLCDCartridge(s) includedDisplay diagonal10.9 cm (4.3")Control typeTouchTouchscreenSound power level (standby)32 dBTouchscreenLUCLUCTouchscreenSound power level (standby)32 dBTouchscreenLUC <t< td=""><td rowspan="3">Ethernet interface typeGigalEthernet LAN *USB port *XUSB connectorUSB *USB 3.2 Gen 1 (3.1 Gen 1) ports quantity1</td><td rowspan="2">Gigabit Ethernet ✓ X</td><td>Depth Height</td><td>505 mm 230 mm</td></t<>	Ethernet interface typeGigalEthernet LAN *USB port *XUSB connectorUSB *USB 3.2 Gen 1 (3.1 Gen 1) ports quantity1	Gigabit Ethernet ✓ X	Depth Height	505 mm 230 mm
quantityIPackage width730 mmEthernet LAN data rates10,100 Mbit/sPackage depth1530 mmPerformancePackage height655 mmBuilt-in display *Package weight45.5 kgDisplayLCDCartridge(s) includedDisplay diagonal10.9 cm (4.3")Control typeTouchTouchscreenSound power level (standby)32 dBTouchscreenLUD <t< td=""><td>Packaging data</td><td></td></t<>			Packaging data	
Package weight45.5 kgBuilt-in display*✓DisplayLCDDisplay diagonal10.9 cm (4.3")Control typeTouchSound power level (standby)32 dBDisplay diagonal✓LCDTouchscreenLCDIntersentLCD <td< td=""><td>-</td><td>5</td><td></td></td<>		-	5	
Built-in display* Image: Construction of the sector of t	Performance			
Control type Touch Other features Sound power level (standby) 32 dB Touchscreen ✓ Logistics data	Display Display diagonal Control type	LCD 10.9 cm (4.3") Touch	Cartridge(s) included	√
Logistics data			Other features	
			Touchscreen	1
Quantity per pack $1 pc(c)$			Logistics data	
Quality per pack 1 pc(s)			Quantity per pack	1 pc(s)



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.