

TP-Link TL-MR6400 wireless router Fast Ethernet Single-band (2.4 GHz) 4G Black

Brand : TP-Link Product code: TL-MR6400

Product name: TL-MR6400

- Share your 4G LTE network with multiple Wi-Fi devices and enjoy download speeds of up to 150 Mbps
- Wireless N speeds of up to 300 Mbps
- Integrated antennas provide stable wireless connections
- Requires no configuration just insert a SIM card and turn it on to enjoy high speed internet access
- LAN/WAN port provides options and flexibility, allowing you to choose your connection type 300 Mbps Wireless N 4G LTE Router

TP-Link TL-MR6400. WAN connection type: RJ-45. Wi-Fi band: Single-band (2.4 GHz), Top Wi-Fi standard: Wi-Fi 4 (802.11n), WLAN data transfer rate (max): 300 Mbit/s. Ethernet LAN interface type: Fast Ethernet, Ethernet LAN data rates: 10,100 Mbit/s, Cabling technology: 10/100Base-T(X). Mobile network generation: 4G, 3G standards: HSPA+, UMTS, 4G standard: LTE. Security algorithms: 64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK





WAN connection		Protocols	
Ethernet WAN * DSL WAN * SIM card slot *	✓ ×	DHCP server Universal Plug and Play (UPnP) Supported network protocols	✓ ✓ IPv4, IPv6
3G/4G USB modem compatibility *	X	Design	
WAN connection type	RJ-45	Product colour	Black
Wireless LAN features		LED indicators	LAN, Power, WLAN
Wi-Fi band * Top Wi-Fi standard *	Single-band (2.4 GHz) Wi-Fi 4 (802.11n)	On/off switch Product type *	✓ Tabletop router
WLAN data transfer rate (max) * Wi-Fi standards	300 Mbit/s 802.11b, 802.11g, Wi-Fi 4 (802.11n)	Packaging content Cables included	LAN (DLAE)
Network		AC adapter included	LAN (RJ-45) ✓
Ethernet LAN * Ethernet LAN interface type * Ethernet LAN data rates 10.100 Mbit/s	·	Manual Quick installation guide Quick start guide	* * * * * * * * * *
Cabling technology	10/100Base-T(X)	Antenna	
Networking standards Port forwarding	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3 ✓	Antenna design * Antennas quantity	External 2
Mobile network		Detachable antenna(s)	✓
Mobile network generation	4G	Features Certification	CE, RoHS
3G	1		CL, NOTIS
4G 3G standards 4G standard UMTS bands supported	HSPA+, UMTS LTE 1900,2100 MHz	Power Power source type * Output voltage Output current	DC 9 V 0.85 A
4G bands supported	800,900,1800,1900,2100,2600 MHz	Operational conditions	
Ports & interfaces Ethernet LAN (RJ-45) ports * USB port * Memory card slot(s) DC-in jack	4 × ×	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	0 - 40 °C -40 - 70 °C 10 - 90% 5 - 90%

Management features		System requirements	
Web-based management Quality of Service (QoS) support Reset button WPS push button	4 4 4	Windows operating systems supported Linux operating systems supported Mac operating systems supported	4 4 4
Security		Mac compatibility	4
Security algorithms	64-bit WEP, 128-bit WEP, WPA, WPA-PSK, WPA2, WPA2-PSK	Weight & dimensions	
		Width	202 mm
Firewall	✓	Depth	141 mm
Stateful Packet Inspection (SPI)	✓	Height	33.6 mm
DoS attack prevention	✓	Packaging data	
Filtering	√	Package width	307 mm
MAC address filtering	✓	Package depth	223 mm
IP address filtering	✓	Package height	70 mm
DMZ support	✓	Package weight	600 g
Protocols		Logistics data	
DHCP client	1	•	
	•	Harmonized System (HS) code	85176990

