Lindy 2m High Speed HDMI Cable, Anthra Line

Brand : Lindy

Product code: 36963

Product name : 2m High Speed HDMI Cable, Anthra Line

2m High Speed HDMI Cable, Anthra Line

Lindy 2m High Speed HDMI Cable, Anthra Line:

From the Lines cable connectivity concept developed by Lindy, Anthra Line HDMI cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line HDMI cables are premium connections that feature triple shielded with 30AWG copper conductors with for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 8bit are supported. Anthra Line HDMI cables are also capable of transmitting 32 channel audio and Dolby True HD.

The HDMI 2.0 specification is supported for 18Gbps bandwidth capacity in cable lengths up to 5m.

Anthra Line HDMI cables are available in lengths from 0.3m to 5m.





Features

Cable length * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Connector 2 gender * Connector 2 form factor Product colour * HDMI version 3D Supported graphics resolutions Supported video modes

Dolby technologies

Audio Return Channel (ARC) HDMI Ethernet channel Data transfer rate Maximum resolution AWG wire size Contact material Connector contacts plating * Connector housing material 2 m HDMI Type A (Standard) HDMI Type A (Standard) Male Male Straight Straight Black, Grey 2.0 1 4096 x 2160 1080p DTS-HD Master Audio, Dolby TrueHD J 1 18 Gbit/s 4096 x 2160 pixels 30

Phosphor copper

Polyvinyl chloride (PVC)

Gold

Features	
Connector material	Gold
Cable material	Copper
Cable type	Round cable
Cable jacket material	Polyvinyl chloride (PVC)
Shield material	Copper
Bending radius (min)	4.8 cm
Colour sampling	4:4:4
Nominal attenuation	300kHz-825MHz 5dB, 825MHz-2.475GHz 5dB, 2.475GHz-4.125GHz 12dB, 4.125GHz-5.1GHz 20dB
Certification	RoHS, REACH, UL, ATC
Quantity per pack *	1 pc(s)
Operational conditions	
Operating temperature (T-T)	-10 - 80 °C
Storage temperature (T-T)	-10 - 80 °C
Weight & dimensions	
Cable diameter	6 mm
Connector 1 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Connector 2 dimensions (WxDxH)	20 x 34.2 x 10.9 mm
Package type	Polybag
Logistics data	
Harmonized System (HS) code	84733080



4002888369633

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.