

ASUS ProArt PA24AC computer monitor 61.2 cm (24.1") 1920 x 1200 pixels WUXGA LED Silver

Brand : ASUS

Product family: ProArt

Product code: 90LM04B0-B01370

Product name : PA24AC



- 24-inch WUXGA 1920 x 1200 IPS display with frameless design
 - 100% of sRGB color gamut, pre-calibrated for excellent color accuracy ($\Delta E < 2$)
 - Support HDR-10 presents HDR (High Dynamic Range) performance
 - ASUS ProArt Calibration technology offers advanced adjustments
 - I/O ports: DP over USB-C™ with 60W Power Delivery, DisplayPort, HDMI, USB 3.0 hub
- 24.1" WUXGA (1920 x 1200) IPS, 16:10, 350 cd/m, 5ms, 100M:1, HDMI(v2.0a) x2, DisplayPort 1.2, USB , 2x2W
- ASUS ProArt PA24AC. Display diagonal: 61.2 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LED, Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Silver

Display		Ports & interfaces	
Display diagonal *	61.2 cm (24.1")	Headphone out *	✓
Display resolution *	1920 x 1200 pixels	Headphone outputs	1
HD type *	WUXGA	HDCP	✓
Native aspect ratio *	16:10	AC (power) in	✓
Display technology *	LED	Ergonomics	
Panel type *	IPS	VESA mounting *	✓
Touchscreen *	✗	Panel mounting interface	100 x 100 mm
Display brightness (typical)	350 cd/m ²	Cable lock slot *	✓
Response time	5 ms	Cable lock slot type	Kensington
Screen shape *	Flat	Height adjustment *	✓
Supported graphics resolutions	1920 x 1200 (WUXGA)	Height adjustment	11 cm
Contrast ratio (typical) *	1000:1	Pivot	✓
Contrast ratio (dynamic)	100000000:1	Pivot angle	-90 - 90°
Maximum refresh rate *	70 Hz	Swivelling	✓
Viewing angle, horizontal	178°	Swivel angle range	-45 - 45°
Viewing angle, vertical	178°	Tilt adjustment	✓
Display number of colours *	16.78 million colours	Tilt angle range	-5 - 23°
Viewable size, horizontal	51.8 cm	Picture-in-Picture	✓
Viewable size, vertical	32.4 cm	LED indicators	✓
Digital horizontal frequency	30 - 85 kHz	Power	
Digital vertical frequency	48 - 70 Hz	Energy efficiency class (SDR) *	G
High Dynamic Range (HDR) supported	✓	Energy efficiency class (HDR) *	G
High Dynamic Range (HDR) technology	High Dynamic Range (HDR) 400	Energy consumption (SDR) per 1000 hours *	28 kWh
Colour depth	8 bit	Energy consumption (HDR) per 1000 hours *	29 kWh
Colour gamut standard	sRGB	Power consumption (standby) *	0.5 W
sRGB coverage (typical)	100%	Power consumption (off)	0.3 W
3D	✗	AC input voltage	100 - 240 V
Performance		AC input frequency	50 - 60 Hz
NVIDIA G-SYNC *	✗	Energy efficiency scale	A to G
AMD FreeSync *	✗	Operational conditions	
VESA Adaptive Sync support	✓	Operating temperature (T-T)	0 - 40 °C
Flicker-free technology	✓	Storage temperature (T-T)	-20 - 60 °C
Low Blue Light technology	✓	Packaging content	
Multimedia		Stand included	✓
Built-in speaker(s) *	✓	Cables included	AC
Built-in camera *	✗		

Multimedia		Packaging content	
Number of speakers	2	Manual	✓
RMS rated power	4 W	Weight & dimensions	
Design		Width (with stand)	532 mm
Market positioning *	Graphics design	Depth (with stand)	202 mm
Product colour *	Silver	Height (with stand)	378 mm
Frameless design	✓	Weight (with stand)	6.5 kg
Feet colour	Silver	Width (without stand)	532 mm
Certification	Energy Star®, BSMI, CB, CCC, CEL level , CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, Mac CompliantPSE, TCO7.0, UkrSEPRO, UL/cUL, VCCI, WEEE, WHQL , MEPS, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, Vietnam MEPS, ICES-3, RCM, VESA DisplayHDR 400	Depth (without stand)	55 mm
		Height (without stand)	349 mm
		Weight (without stand)	4.28 kg
		Height (max)	48.8 cm
Ports & interfaces		Packaging data	
USB hub version	3.2 Gen 1 (3.1 Gen 1)	Package width	650 mm
USB upstream port type	USB Type-C	Package depth	430 mm
Number of upstream ports	1	Package height	260 mm
Number of USB Type-C upstream ports quantity	1	Package weight	9 kg
USB Type-A downstream ports quantity	4	Package type	Box
USB Type-C downstream ports quantity	1	Sustainability	
DVI port	✗	European Product Registry for Energy Labelling (EPREL) code	387775
HDMI ports quantity	2	Logistics data	
HDMI version	2.0a	Harmonized System (HS) code	85285210
DisplayPorts quantity	1	Other features	
DisplayPort version	1.2	On/off switch	✓
		Rotating	✗
		TV tuner integrated	✗
		Picture-by-Picture (PbP)	✓



4718017080835



0192876088111



192876088111



4718017080804

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.