Lindy 2m DisplayPort to HDMI 10.2G Cable

Brand : Lindy

Product code: 36922

Product name : 2m DisplayPort to HDMI 10.2G Cable

- Connects a DisplayPort equipped device to a 4K UHD HDMI display or projector
- Supports resolutions up to 3840x2160@30Hz
- Supports video mirroring and extended desktop modes
- Audio pass-through if supported by the video source
- 2 year warranty
2m DisplayPort to HDMI 10.2G Cable

Lindy 2m DisplayPort to HDMI 10.2G Cable:

The Lindy DisplayPort to HDMI Cable is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI display. Supporting 4K UHD resolutions up to 3840x2160@30Hz, this cable is ideal for ensuring video is displayed in superior clarity. This cable can also be used to add another display to extend the available desktop workspace and increase productivity, great for use in residential or workplace office setups.

The DisplayPort to HDMI Cable supports uncompressed 7.1 Audio and compressed Audio such as DTS-HD Master Audio, Dolby TrueHD. Please note that audio output over HDMI is only supported when the graphics card of the laptop or desktop computer supports audio output over DisplayPort.

Features

Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Gold
Cable length *	2 m
Connector 1 *	DisplayPort
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Male
HDMI version	1.4
DisplayPort version	1.2
Maximum resolution	3840 x 2160 pixels
Supported graphics resolutions	3840 x 2160
Supported video modes	1080p
Data transfer rate	10.2 Gbit/s
Maximum refresh rate	30 Hz
Bend radius (min)	7.3 cm
Product colour	Black
Conductor material	Tinned copper
Nominal attenuation	100MHz~450MHz -2.44--5.099dB 450MHz~8100MHz -5.094~32.906dB
Jacket material	Polyvinyl chloride (PVC)

Features

Cable type	Round cable
Connector housing material	Polyvinyl chloride (PVC) / Acrylonitrile butadiene styrene (ABS)
Connector material	Gold
Contact material	Copper
AWG wire size	28
Colour depth	8 bit
Colour sampling	4:4:4
Cable shielding	Aluminium braid
Certification	CE, UKCA, FCC, RoHS, REACH, UL, California

Operational conditions

Operating temperature (T-T)	0 - 45 °C
Storage temperature (T-T)	-10 - 80 °C

Weight & dimensions

Cable diameter	7.3 mm
Connector 1 dimensions (WxDxH)	36.4 x 20.5 x 9.4 mm
Connector 2 dimensions (WxDxH)	37.5 x 20.5 x 10.5 mm

Packaging data

Quantity per pack	1 pc(s)
Package type	Polybag

Logistics data

Harmonized System (HS) code	84733080

4002888369220