Manhattan Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag

Brand : Manhattan

Product name : Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag

Product code: 151528

Mini DisplayPort to HDMI Adapter Cable, 1080p, Passive, Male to Female, 12cm, Black, Polybag

Manhattan Mini DisplayPort 1.2 to HDMI Adapter Cable, 1080p@60Hz, 12cm, Male to Female, Black, Equivalent to MDP2HDMI, Three Year Warranty, Polybag:

Easily connect a Mini DisplayPort source to an HDMI cable.

The Manhattan Passive Mini DisplayPort to HDMI Adapter establishes a fast, simple and convenient connection between a Mini DisplayPort media source and an HDMI display. This passive adapter requires a DP++ (dual-mode) video/graphics cards on the media source to regenerate the signal and ensure the best connection to an HD display. Ideal for presentations, retail displays and other uses, this single solution is easy and quick to install and requires no complicated configuration or setup. With the Manhattan Passive Mini DisplayPort to HDMI Adapter, users will be able to fully realise the investment, value and service life of HDMI displays. It offers a passive, compact and integrated solution that eliminates unnecessary cables, tangles and clutter to keep installations and workspaces neat and orderly.

Features

Connector 1 form factor	Straight
Connector 2 form factor	Straight
Connector contacts plating	Nickel
Cable length *	0.12 m
Connector 1 *	Mini DisplayPort
Connector 2 *	HDMI Type A (Standard)
Connector 1 gender *	Male
Connector 2 gender *	Female
DisplayPort version	1.2
Dual Link DVI	✔
Maximum resolution	1920 x 1200 pixels
Supported video modes	1080p
Data transfer rate	10.8 Gbit/s
Product colour	Black
AWG wire size	30
Colour depth	10 bit

Features

Converter type	Passive video converter
Cable shielding	Aluminium mylar foil
Connector gender	Male/Female
Certification	UL 20276

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C

Weight & dimensions

Weight	53 g
Width	20 mm
Depth	170 mm
Height	11 mm

Packaging data

Quantity per pack	1 pc(s)
Package type	Polybag

Logistics data

Harmonized System (HS) code	84733080

0766623151528

766623151528