



2m USB Type C to HDMI 4K60 Adapter Cable with HDR

No.: 43292

Connect an HDMI display to your computer's USB Type C port

Description

- Connect a 4K HDMI display to your computer's USB Type C port
- Supports HDMI resolutions up to 4K 4960x2160@60Hz
- High Dynamic Range support provides deeper blacks, brighter whites and a wider colour gamut
- Requires DisplayPort Alternate Mode support by the USB Port/Bus
- 2 Year Warranty

Lindy USB Type C to HDMI 4K60 Adapter Cable with HDR allows users to easily add external video capabilities to a computer featuring the USB Type C port with additional support for DisplayPort Alternate Mode. The HDMI connector of the adapter cable can be directly connected to the HDMI display - while the 2m cable allows for a more flexible positioning of the HDMI display than when using a box converter - perfect for a simple and adaptable installation.

With support for resolutions up to 4096x2160@60Hz and with additional support for High Dynamic Range, 4K content can be viewed with crystal clear clarity, enhanced contrast and more lifelike colour. These cables are great for creating eye-catching retail displays, innovative working environments or immersive video playback in sports bars and home cinema installations, while support for uncompressed multi-channel audio allows for an impressive three-dimensional surround sound performance to compliment detailed, clear video.

This cable is powered by the USB Bus, therefore no external power supply is needed and with 'Plug and Play' installation, this converter cable can be installed into an AV ecosystem with minimum difficulty, ideal for both professional and first time users.

Technical details

Connectors

- Connector A: USB Type C Male
- Connector B: HDMI Type A Male
- Housing Material: Type C: PVC, HDMI: ABS
- Connector Plating: Gold plating
- Pin Construction: Phosphor Bronze
- Pin Plating: Gold plating

- Dimensions (approx.) WxDxH:
A: 12.6x24x6.6mm (0.5x0.94x0.26in)
B: 22x45.1x12mm (0.87x1.77x0.47in)

Cable construction

- Length: 2m (6.56ft)
- Standard: HDMI 2.0
- Colour: Black
- Type: Round
- Jacket Diameter: 5.0mm (0.2in)
- Jacket Material: PVC
- Conductor Material: Tinned Copper
- Conductor Gauge: 32AWG
- Shielding: AL/MG Braid 85%

Specifications

- Chipset: ITE6563
- Supported Bandwidth: 21.6Gbps
- Power Delivery: -
- Maximum Resolution: 4096x2160@60Hz 4:4:4 8bit / 4:2:2 12bit
- Nominal Attenuation: 0.1MHz-6MHz<12DB
- Minimum Bend Radius: 47mm (1.85in)
- Operating Temperature: 0°C - 35°C (32°F - 95°F)
- Storage Temperature: 0°C - 45°C (32°F - 113°F)

Miscellaneous

- Packaging Type: Polybag
- Warranty (Years): 2
- Certificated: CE, FCC, RoHS, REACH & UL

Purchasing information

- No.: 43292
- EAN: 4002888432924

This product is also available in other lengths:

- 43291 - 1m (3.28ft)
- 43292 - 2m (6.56ft)
- 43293 - 3m (9.84ft)