

ZYXEL

Zyxel GS1900-48-GB0102F network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Brand : Zyxel

Product code: GS1900-48-GB0102F

Product name : GS1900-48-GB0102F

48-port GbE Smart Managed Switch

[Zyxel GS1900-48-GB0102F network switch Managed L2 Gigabit Ethernet \(10/100/1000\) Black:](#)

Simple, Fast and Smart Managed Switches for Small Business Connectivity

The Zyxel GS1900 Series of 8/16/24/48-port GbE Smart Managed Switch with Gigabit speed and essential managing functions bring your business network more flexibility and connectivity. The 1900 Series consists of eight (8) models—the GS1900-8, GS1900-8HP, GS1900-16, GS1900-24E, GS1900-24, GS1900-24HP, GS1900-48 and GS1900-48HP. Providing GbE switches with powersaving functions, fanless design and full IPv6 support ensure your network to be ready for future expansions. In addition, the PoE models GS1900-8HP/24HP/48HP Gigabit switch complies with the IEEE 802.3at Power over Ethernet (PoE) Plus standard. The complete GS1900 Series has been designed with useful features and advanced performances that empower your networks with speed and security as well as silent operation in your office environments.

Management features		Design	
Switch type *	Managed	Rack mounting *	✓
Switch layer	L2	Product colour	Black
Quality of Service (QoS) support	✓	Performance	
Ports & interfaces		Firmware upgradeable	✓
Basic switching RJ-45 Ethernet ports quantity *	48	Power over Ethernet (PoE)	
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE) *	✗
SFP module slots quantity	2	Operational conditions	
Power connector	AC-in jack	Operating temperature (T-T)	0 - 50 °C
Network		Storage temperature (T-T)	-40 - 70 °C
Networking standards *	IEEE 802.1af, IEEE 802.1D, IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x	Operating relative humidity (H-H)	10 - 95%
10G support *	✗	Heat dissipation	126 BTU/h
Port mirroring	✓	Weight & dimensions	
Data transmission		Width	440 mm
Switching capacity *	100 Gbit/s	Depth	200 mm
Throughput	74 Mpps	Height	44 mm
MAC address table *	8000 entries	Weight	29 kg
Jumbo frames support	✓	Packaging data	
Jumbo frames	9000	Package width	509 mm
Security		Package depth	292 mm
DHCP features	DHCP client	Package height	93 mm
IGMP snooping	✓	Package weight	4.3 kg
Security algorithms	SNMP, SNMPv2, SNMPv3	Logistics data	
		Harmonized System (HS) code	85176990



4718937621262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.