



D-Link DGS-1210-52 network switch Managed L2 Gigabit Ethernet (10/100/1000) 1U Black

Brand : D-Link

Product code: DGS-1210-52

Product name : DGS-1210-52

48 x 10/100/1000 Mbps, 4 x dual-speed SFP, 104 Gbps, 77.4 Mpps, 47.1 dB(A), 43.5 W, 1U
D-Link DGS-1210-52. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 48. Full duplex. MAC address table: 16000 entries, Switching capacity: 104 Gbit/s. Networking standards: IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x. Power connector: DC-in jack. Rack mounting, Form factor: 1U



Management features		Technical details	
Switch type *	Managed	Shipping (inner) case height	38.3 cm
Switch layer	L2	Shipping (inner) case width	31.4 cm
Quality of Service (QoS) support	✓	Shipping (inner) case length	56.2 cm
Ports & interfaces		Shipping (inner) case net weight	13.5 kg
Basic switching RJ-45 Ethernet ports quantity *	48	Products per shipping (inner) case	3 pc(s)
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Pallet gross weight (air)	285 kg
Gigabit Ethernet (copper) ports quantity	48	Master (outer) cases per pallet (air)	18 pc(s)
SFP/SFP+ slots quantity	4	Products per pallet (air)	54 pc(s)
SFP module slots quantity	4	Pallet gross length	110 cm
Power connector	DC-in jack	Pallet gross width	120 cm
Network		Pallet height (air)	128.4 cm
Networking standards *	IEEE 802.1p, IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3u, IEEE 802.3x	Pallet gross weight (sea)	437.6 kg
10G support *	✗	Master (outer) cases per pallet (sea)	30 pc(s)
Copper ethernet cabling technology	1000BASE-T, 100BASE-TX, 10GBASE-T	Products per pallet (sea)	90 pc(s)
Port mirroring	✓	Pallet height (sea)	2.05 m
Full duplex	✓	Shipping (inner) case gross weight	14.4 kg
Flow control support	✓	Power	
Link aggregation	✓	AC input voltage	100 - 240 V
Auto MDI/MDI-X	✓	AC input frequency	50 - 60 Hz
Spanning tree protocol	✓	Power consumption (typical)	43.5 W
Data transmission		Power over Ethernet (PoE)	
Supported data transfer rates	10/100/1000Mbps	Power over Ethernet (PoE) *	✗
Switching capacity *	104 Gbit/s	Operational conditions	
MAC address table *	16000 entries	Operating temperature (T-T)	-5 - 50 °C
Maximum data transfer rate	1 Gbit/s	Storage temperature (T-T)	-20 - 70 °C
Packet buffer memory	1 MB	Operating relative humidity (H-H)	0 - 95%
Security		Storage relative humidity (H-H)	0 - 95%
IGMP snooping	✓	Weight & dimensions	
Protocols		Width	440 mm
Supported network protocols	IPv4 / IPv6	Depth	250 mm
Design		Height	44 mm
Rack mounting *	✓	Weight	4.1 kg
Form factor	1U	Packaging data	
Product colour	Black	Package width	354 mm
LED indicators	Link, Status	Package depth	552 mm
Number of fans	2 fan(s)	Package height	98 mm
		Package weight	4.5 kg
		Logistics data	
		Harmonized System (HS) code	85176990

Design

Safety	cUL, CE LVD
Certification	FCC, CE, VCCI, ICES-003

Other features

Packet transfer speed	77.4 Mpps
Power LED	✓

Performance

Flash memory	16 MB
Noise level	47.1 dB
Mean time between failures (MTBF)	201.517 h



0790069373169



790069373169




0790069373138



790069373138



0790069373121



790069373121

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.