

# Allied Telesis AT-GS950/16-50 Managed L2 Gigabit Ethernet (10/100/1000) 1U White



**Brand :** Allied Telesis

**Product code:** 990-003645-50

**Product name :** AT-GS950/16-50

16 port 10/100/1000TX WebSmart Switch with 2 x 100/1000 SFP bays (Eco version)

[Allied Telesis AT-GS950/16-50 Managed L2 Gigabit Ethernet \(10/100/1000\) 1U White:](#)

16-port 10/100/1000T eco-friendly WebSmart switch with 2 SFP combo ports  
 Allied Telesis AT-GS950/16-50. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16, Console port: RJ-45. MAC address table: 8000 entries. Networking standards: IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3u, IEEE.... Power connector: DC-in jack. Rack mounting, Form factor: 1U

Management features		Design	
Switch type *	Managed	Form factor	1U
Switch layer	L2	Product colour	White
Quality of Service (QoS) support	✓	LED indicators	✓
Web-based management	✓	Certification	UL 1950 FCC/EN55022 VCCI C-Tick EN60950 (TUV) EN55024 CE
Ports & interfaces		Performance	
Basic switching RJ-45 Ethernet ports quantity *	16	Internal memory	8 MB
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Flash memory	2 MB
Combo SFP ports quantity	2	Power	
Console port	RJ-45	AC input voltage	100 - 240 V
Power connector	DC-in jack	AC input frequency	50 - 60 Hz
Network		Input current	0.3 A
Networking standards *	IEEE 802.1D, IEEE 802.1s, IEEE 802.1w, IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE)	
Copper ethernet cabling technology	1000BASE-T, 100BASE-T, 10GBASE-T	Power over Ethernet (PoE) *	✗
Port mirroring	✓	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	0 - 40 °C
Link aggregation	✓	Storage temperature (T-T)	-25 - 70 °C
Auto MDI/MDI-X	✓	Operating relative humidity (H-H)	5 - 90%
Data transmission		Storage relative humidity (H-H)	5 - 95%
Throughput	1488 Mpps	Weight & dimensions	
MAC address table *	8000 entries	Width	352 mm
Packet buffer memory	0.5 MB	Depth	256 mm
Design		Height	43.2 mm
Rack mounting *	✓	Weight	2.38 kg
Stackable *	✗	Logistics data	
		Harmonized System (HS) code	85176990



0767035178424



767035178424

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.