Manhattan HDMI Switch 2-Port, 1080p, Connects x2 HDMI sources to x1 display, Automatic and Manual Switching (via button), No external power required, Black, Three Year Warranty, Blister

Brand : Manhattan

Product code: 207911

Product name : HDMI Switch 2-Port, 1080p, Connects x2 HDMI sources to x1 display, Automatic and Manual Switching (via button), No external power required, Black, Three Year Warranty, Blister

- Connects two HD video sources to a single HDMI display
- Supports video amplifier bandwidth up to 250 MHz and 2.5 Gbps per channel (7.5 Gbps total) for 1080p displays
- 1080p resolution, 3D, Deep colour
- Supports 36-bit Deep colour (12-bits per channel), 4:4:4 chroma subsampling
- Supports automatic switching (when an HD signal is detected) and manual switching (between sources with the push of a button)
- Supports LPCM, DTS Digital, DTS-HD Master Audio and Dolby TrueHD audio
- Supports 3D video and 8-bit (24-bits total) Deep colour
- Supports video amplifier bandwidth up to 2.5 Gbps for a 1080p display
- Works with PlayStation and Xbox game systems, Blu-ray players, set-top boxes, satellite receivers and more
- HDCP compliant
- Plug-and-Play
- Plug and play: no special setup, power or remote requirements
- Gold-plated contacts
- Gold-plated contacts for corrosion-free connections
- Three-year warranty
HDMI 1080p Switch 2-Port, Automatic and Manual Switching, Black

Ports & interfaces

Video port type *	HDMI
HDMI version	1.3b
HDMI in	2
Number of HDMI outputs	1

Features

Material	Plastic
Product colour	Black
Plug and Play	✓
HDCP	✓
Maximum operating distance	5 m
Supported video modes	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Bandwidth	2.5 Gbit/s
LED indicators	Activity, Power
Bandwidth	250 MHz
Connector contacts plating	Gold
3D	✓
HD type	Full HD
Audio decoders	DTS, DTS-HD Master Audio, Dolby TrueHD
Display Data Channel (DDC) input	5 V

Certificates

Certification	CE, FCC

Weight & dimensions

Width	51 mm
Depth	51 mm
Height	15 mm
Weight	30 g

Packaging content

Quantity per pack	1 pc(s)
Quick start guide	✓

Operational conditions

Operating temperature (T-T)	0 - 40 °C
Storage temperature (T-T)	-20 - 60 °C
Operating relative humidity (H-H)	0 - 96%

Sustainability

Sustainability certificates	RoHS

Technical details

Compliance certificates	RoHS

Logistics data

Harmonized System (HS) code	85176990

0766623207911

766623207911