Epson WorkForce DS-80W

Brand : Epson Product family: WorkForce Product code: B11B253402

Product name: WorkForce

DS-80W

- Scan anywhere: Small, lightweight design
- USB cable or integrated battery power: Scan up to 300 pages between battery charges
- Fast scanning speeds: At up to four seconds per page (8.5ppm)
- Simplify your workload: Continuous scanning with automatic feed mode
- Includes a range of software: Document Capture Pro 2, Epson Scan 2.0 and TWAIN driver support WorkForce DS-80W


Epson WorkForce DS-80W. Maximum scan size: $216 \times 1828 \text{ mm}$, Optical scanning resolution: $600 \times 600 \text{ DPI}$, Input colour depth: 48 bit. Scanner type: Handheld scanner, Product colour: White, Display: LCD. Sensor type: CIS, Daily duty cycle (max): 300 pages, Light source: ReadyScan LED. Auto document feeder (ADF) input capacity: 1 sheets. Maximum ISO A-series paper size: A4, Scanning media types supported: Business Card, Plastic Card, Post Card(JPN), Paper tray media weight: $35 - 270 \text{ g/m}^2$





Scanning		Network	
Maximum scan size * Optical scanning resolution * Colour scanning Duplex scanning * Input colour depth Output colour depth Input greyscale depth	216 x 1828 mm 600 x 600 DPI	Wi-Fi	✓
		System requirements	
		Compatible operating systems	Mac OS 10.6+, Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Server 2003, Windows Server 2008 (32/64 Bit), Windows Server 2012 R2, Windows Server 2016, Windows Vista, Windows XP
Output greyscale depth Output monochrome depth Scan speed (b/w, low res, A4)	8 bit 8 bit 4 sec/page	Windows operating systems supported	Windows 10, Windows 7, Windows 8, Windows 8.1, Windows Vista, Windows XP
Scan speed (colour, low res, A4)	4 sec/page		Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12
Design			Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks
Scanner type * Product colour * Display	Handheld scanner White LCD	Mac operating systems supported	
Colour display Built-in display *	X ✓	Server operating systems supported	Windows Server 2003, Windows Server 2008, Windows Server 2008 x64, Windows Server 2012 R2,
Performance			Windows Server 2016
Sensor type *	CIS	Operational conditions	
Light source	ReadyScan LED	Operating temperature (T-T)	5 - 35 °C
Scan file formats	BMP, JPEG, PDF, PNG, TIFF	Storage temperature (T-T)	-25 - 60 °C
Daily duty cycle (max) * Scan drivers	300 pages TWAIN, WIA, SANE, ICA	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 85% 10 - 90%
	IWAIN, WIA, SANE, ICA	, , ,	10 - 90 %
Input capacity		Weight & dimensions	
Auto document feeder (ADF) input capacity	1 sheets	Width	272 mm
. ,		Depth Height	47 mm 34 mm
Paper handling	Budiana Carl Bladia Carl Bad	Weight	300 g
Scanning media types supported	Business Card, Plastic Card, Post Card(JPN)	Packaging content	500 g
Maximum ISO A-series paper size *	A4	Cables included	USB
Paper tray media weight	35 - 270 g/m²		Document Capture Pro 2.0, Epson
Auto Document Feeder (ADF) media weight	35 - 270 g/m²	Bundled software	Scan 2
Ports & interfaces		Other features	
USB port *	1	Output resolutions	600 dpi
USB version	2.0	Image formats supported	BMP, JPEG, TIFF, PNG

Ports & interfaces		Technical details	
Standard interfaces	USB 2.0, Wireless LAN	Master (outer) case GTIN (EAN/UPC)	8715946663005
Power		Logistics data	
Power supply type *	USB	Products per pallet	360 pc(s)
Packaging data		Master (outer) case length Master (outer) case height	360 mm 320 mm
Quantity per pack Package width Package depth Package height Package weight	1 pc(s) 141 mm 330 mm 67 mm 597 g	Master (outer) case width Pallet gross length Pallet gross width Pallet gross height Products per master (outer) case	350 mm 120 cm 80 cm 171 cm 10 pc(s)
Features		Products per pallet layer	60 pc(s)
Country of origin	China	Products per pallet layer (UK) Products per pallet (UK) Pallet length (UK) Pallet width (UK) Pallet height (UK) Harmonized System (HS) code	60 pc(s) 360 pc(s) 120 cm 100 cm 171 cm 84716070



8715946662848

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.