Everyday ™ Mono Remanufactured Toner by Xerox compatible with HP 12A (Q2612A), Standard capacity

Brand : Xerox Product family: Everyday Product code: 003R99628

Product name: Everyday™ Mono Remanufactured Toner by Xerox compatible with HP 12A (Q2612A), Standard capacity Experimental control of the control

Everyday™ Mono Remanufactured Toner by Xerox compatible with HP 12A (Q2612A), Standard capacity

Everyday $^{\text{TM}}$ Mono Remanufactured Toner by Xerox compatible with HP 12A (Q2612A), Standard capacity:

Being environmentally responsible is simply the best way to do business, because it positively impacts the health of our planet, your company and your people. Everyday Remanufactured Toner by Xerox has the lowest carbon footprint than any single-use toner cartridge. Because you shouldn't have to choose between doing your part to reduce your eco-impact and your toner costs. And compatibility with the most popular printer brands means you can enjoy benchmark Xerox quality and stewardship no matter what kind of printer you have.

Everyday $^{\text{TM}}$ Mono Remanufactured Toner by compatible with HP 12A (Q2612A), Standard capacity. Black toner page yield: 2000 pages, Printing colours: Black, Quantity per pack: 1 pc(s)

Features		Operational conditions	
Compatibility *	HP LaserJet 1010/1012/1015/1018 HP LaserJet 3015/3020/3030/305x HP LaserJet 1020/1022	Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	30 - 70% 0 - 35 °C 35 - 85%
Quantity per pack *	1 pc(s) Standard Yield 2000 pages Compatible Black HP Single pack HP 12A Q2612A Vietnam RoHS, REACH SVHC, CE MARK	Weight & dimensions	
Cartridge capacity Black toner page yield * Type * Printing colours * Brand compatibility * Supply type * Replacement for		Weight Package width Package depth Package height Package weight Package type Logistics data	910 g 160 mm 370 mm 120 mm 976.7 g Box
OEM code Country of origin		Harmonized System (HS) code Products per master (outer) case	8443.99.1000 15 pc(s)
Certification	STMC, ISO 9001:2015, ISO 14001:2015	Other features	
Operational conditions		Colour	1
Operating temperature (T-T)	17 - 25 °C		





5017534996285

5715063174296

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.