Epson TM-M30II-S (012) 203 x 203 DPI Wired Direct thermal POS printer

Brand : Epson **Product code:** C31CH63012

Product name: TM-M30II-S (012)

Epson TM-M30II-S (012). Print technology: Direct thermal, Type: POS printer, Maximum resolution: 203 x 203 DPI. Maximum roll diameter: 8.3 cm, Supported paper width: 58 mm - 80 mm (Breite), Maximum printing width: 8 cm. Connectivity technology: Wired, USB connector: USB Type-A / USB Type-B. Compatible memory cards: MicroSD (TransFlash), Sound pressure level (printing): 55 dB, Mean time between failures (MTBF): 360000 h. Product colour: White





Printing		Design	
Maximum resolution Print speed Print speed (receipt) Printing characters Character sets Print technology *	203 x 203 DPI 250 mm/sec 250 mm/sec Text, Graphic, Barcode ANK Direct thermal	Product colour *	White
		Power	
		Power source type *	AC
		Power plug type	Type C
		Operational conditions	
Type *	POS printer	Operating temperature (T-T)	5 - 45 °C
Paper handling		Storage temperature (T-T)	-20 - 60 °C
Maximum roll diameter	8.3 cm	Operating relative humidity (H-H) Storage relative humidity (H-H)	10 - 90%
Supported paper width	58 mm - 80 mm (Breite)		10 - 90%
Maximum printing width	8 cm	Weight & dimensions	
Ports & interfaces		Width	140 mm
USB port *	1	Depth	214 mm
USB 2.0 ports quantity	4	Height Weight	255 mm 2.9 kg
USB connector	USB Type-A / USB Type-B	J	2.9 kg
Connectivity technology *	Wired	Packaging data	1(-)
Network		Quantity per pack Package width	1 pc(s) 210 mm
Ethernet LAN *	1	Package depth	315 mm
Wi-Fi *	×	Package height	325 mm
Features		Package weight	3.83 kg
Card reader integrated	✓ MicroSD (TransFlash) 55 dB 360000 h	Print technology	
Compatible memory cards		Column capacity	48/57
Sound pressure level (printing) Mean time between failures (MTBF)		Logistics data	
Cutter	✓	Harmonized System (HS) code	84433210
Half-cutter	1	Products per pallet	72 pc(s)
Autocutter durability	2.2 million cuts	Products per pallet (UK)	96 pc(s)
Tablet charge & sync	150 km Philippines Vertical	Technical details	
Print head life		Font styles	ANK
Country of origin Mounting position		Lifetime	17000000 lines
Built-in sensors details	Paper End Sensor, Paper Near End Sensor, Papier-Sensor	Other features	
		Buffer size	12 KB
		Mean cycles between failures (MCBF)	65000000
		Print head life	150.000.000 Impulse
		Print head life	150 million characters



8715946688817

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.