



**Manhattan USB-C to USB-C Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Power Delivery up to 60W, Hi-Speed USB, Lifetime Warranty, Polybag**



**Brand :** Manhattan

**Product code:** 356213

**Product name :** USB-C to USB-C Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Power Delivery up to 60W, Hi-Speed USB, Lifetime Warranty, Polybag

- USB-C male to USB-C male for charging a USB-C device from a USB-C port
  - Supports USB Power Delivery (PD) up to 60 W
  - Does not support data transmission
  - Curly, retracting design to eliminate annoying cable tangles and clutter
  - Ideal for Manhattan charging cabinets, charging carts and car chargers
  - Expands from compact 35 cm (14 in.) to extended 1 m (3 ft.)
  - Convenient 90° angled plugs for easy connection in inconvenient places like tight corners or hard-to-reach ports
  - Charges a USB-C powered device such as a notebook, Macbook Pro®, iPad® Pro, smartphone, GPS, tablet, PS5 controller, and more
  - Pure bare copper wire for maximum conductivity
  - Corrosion-resistant contacts
  - Flexible, durable PVC jacket
  - Supports current up to 3 A
- USB-C to USB-C Cable, 1m, Male to Male, Black, 480 Mbps (USB 2.0), Tangle Resistant Curly Design, Angled Connectors, Ideal for Charging Cabinets/Carts, Power Delivery up to 60W, Hi-Speed USB, Lifetime Warranty, Polybag

Features		Features	
Cable length *	1 m	Certification	CE RoHS UL 20233 REACH
Connector 1 *	USB C	<b>Weight &amp; dimensions</b>	
Connector 2 *	USB C	Cable diameter	3.5 mm
Connector 1 gender *	Male	Weight	22 g
Connector 2 gender *	Male	<b>Packaging data</b>	
Connector 1 form factor	Angled	Quantity per pack *	1 pc(s)
Connector 2 form factor	Angled	Package weight	24 g
AWG wire size	24/30	Package type	Polybag
Connector contacts plating	Nickel	<b>Operational conditions</b>	
Cable jacket material	Polyvinyl chloride (PVC)	Operating temperature (T-T)	0 - 45 °C
Product colour *	Black	Storage temperature (T-T)	-10 - 70 °C



0766623356213



766623356213

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.