

EIZO FlexScan EV2456-BK LED display 61.2 cm (24.1") 1920 x 1200 pixels WUXGA Black

Brand: EIZO Product family: FlexScan Product code: EV2456-BK

Product name: EV2456-BK

 $24.1^{\prime\prime}\ LCD,\ IPS,\ 1920x1200,\ 1000:1,\ 350\ cd/m^2,\ 5ms,\ 2W\ RMS,\ USB-hub\ v3.0,\ DisplayPort,\ HDMI,\ DVI-D,\ D-Sub\ mini,\ Black$

EIZO FlexScan EV2456-BK. Display diagonal: 61.2 cm (24.1"), Display resolution: 1920 x 1200 pixels, HD type: WUXGA, Display technology: LED. Display: LCD. Response time: 5 ms, Native aspect ratio: 16:10, Viewing angle, horizontal: 178°, Viewing angle, vertical: 178°. Built-in speaker(s). Built-in USB hub, USB hub version: 3.2 Gen 1 (3.1 Gen 1). VESA mounting, Height adjustment. Product colour: Black











Display		Ergonomics	
Display diagonal *	61.2 cm (24.1")	Height adjustment *	✓
Display resolution *	1920 x 1200 pixels	Height adjustment	15.9 cm
HD type *	WUXGA	Pivot	✓
Native aspect ratio *	16:10	Swivelling	✓
Display technology *	LED	Tilt adjustment	✓
Panel type *	IPS	On Screen Display (OSD)	✓
Touchscreen *	×		Simplified Chinese, Traditional
Display brightness (typical)	350 cd/m ²	On Screen Display (OSD) languages	Chinese, German, English, Spanish, French, Italian, Japanese, Swedish
Response time	5 ms	Number of OSD languages	9
Screen shape *	Flat	Plug and Play	1
	640 x 480 (VGA), 720 x 400, 800 x 600 (SVGA), 1024 x 768 (XGA),	Power	•
Supported graphics resolutions	1280 x 1024 (SXGA), 1600 x 1200		D
	(UXGA), 1680 x 1050 (WSXGA+),	Energy efficiency class (SDR) *	_
Contrast ratio (typical) *	1920 x 1200 (WUXGA) 1000:1	Energy consumption (SDR) per 1000 hours *	14 kWh
Viewing angle, horizontal	178°	Power consumption (typical) *	13.5 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours *	16.78 million colours	Power consumption (max)	44 W
Pixel pitch	0.27 x 0.27 mm	AC input voltage	100 - 240 V
Horizontal scan range	31 - 81 kHz	AC input frequency	50 - 60 Hz
Vertical scan range	55 - 76 Hz	Energy efficiency scale	A to G
Viewable size, horizontal	51.8 cm	Operational conditions	
Viewable size, vertical	32.4 cm	Operating temperature (T-T)	5 - 35 °C
3D	×	Operating relative humidity (H-H)	20 - 80%
Separate H/V sync	✓	, , ,	20 00%
Performance		Packaging content	
NVIDIA G-SYNC *	×	Stand included	√
AMD FreeSync *	- Ĉ	Cables included	AC, USB
AND TICESTIC		Quick start guide	✓

Multimedia		Packaging content	
Built-in speaker(s) * Built-in camera *	Manual	✓	
		Weight & dimensions	
Number of speakers	2	Width (with stand)	531 mm
RMS rated power	2 W	Depth (with stand)	190 mm
Design		Height (with stand)	351.4 mm
Product colour * Certification	Black CE, UKCA, CB, TÜV/GS, TÜV/Ergonomics (including ISO 9241-307), TCO Certified Generation 9, EPEAT 2018 (US), TÜV/Blue Low Light Content, TÜV/Flicker Free, RCM, cTÜVUS, FCC-B, CAN ICES-3 (B), TÜV/S, PSE, VCCI-B, EPA ENERGY STAR, ROHS, WEEE, China ROHS, CCC	Weight (with stand)	5.7 kg
		Width (without stand) Depth (without stand)	531 mm 45.5 mm
		Height (without stand)	341.9 mm
		Weight (without stand)	3.7 kg
		Packaging data	· J
		User Guide on CD-ROM	√
Donto C introfesso	WEEE, Clillid ROBS, CCC	Sustainability	
Ports & interfaces		Sustainability compliance	✓
Built-in USB hub * USB hub version	√ 2.2 Con 1 /2.1 Con 1\	Sustainability certificates	ENERGY STAR, EPEAT Bronze, TCO
USB upstream port type	3.2 Gen 1 (3.1 Gen 1) USB Type-B 1	European Product Registry for Energy Labelling (EPREL) code	346702
Number of upstream ports		Logistics data	
USB Type-A downstream ports quantity	2	Harmonized System (HS) code	85285210
VGA (D-Sub) ports quantity	1	Thin Client	
DVI port	√	Thin client installed	×
DVI-D ports quantity HDMI ports quantity	1 1	Technical details	
DisplayPorts quantity	1		CB, CCC, CE, China RoHS, Federal
Headphone out *	√	Compliance certificates	Communications Commission (FCC),
Headphone outputs	1	compliance ceremeates	ICES, PSE, RCM, RoHS, TÜV mark, UKCA, VCCI, WEEE, cTUVus
Headphone connectivity	3.5 mm	Other features	oken, veel, well, crovus
HDCP	✓		100
Ergonomics		Display On/off switch	LCD /
VESA mounting *	✓	TV tuner integrated	×
Panel mounting interface	100 x 100 mm	No flickering	√
Cable lock slot *	X	Power management	✓



4995047049722

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.