



APC SMC1000I-2UC uninterruptible power supply (UPS) Line-Interactive 1 kVA 600 W 4 AC outlet(s)



Brand : APC

Product code: SMC1000I-2UC

Product name : SMC1000I-2UC

1 kVA, 600W, 85-136V, 50/60Hz, 680J, 432x406x86mm, 20.52kg, Black

APC SMC1000I-2UC. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 600 W.

AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery

technology: Sealed Lead Acid (VRLA), Battery life (max): 6 year(s), Battery recharge time: 3 h. Form

factor: Rackmount, Product colour: Black, Rack capacity: 2U. Width: 432 mm, Depth: 406 mm, Height: 86

mm



Features		Battery	
UPS topology *	Line-Interactive	Battery recharge time	3 h
Output power capacity *	1 kVA	Replacement battery cartridge	APCRBC124
Output power *	600 W	Design	
Waveform *	Sine	Form factor *	Rackmount
Input operation voltage (min) *	170 V	Rack capacity	2U
Input operation voltage (max) *	300 V	Cable length	2.44 m
Input frequency *	50/60 Hz	Product colour *	Black
Output operation voltage (min)	220 V	Display type	LCD
Output operation voltage (max)	240 V	Certification	CSA, CSA C22.2 No. 107.1, FCC Part 15 Class B, ICES-003, UL 1778, REACH
Output frequency	50/60 Hz	Operational conditions	
Automatic Voltage Regulation (AVR) ✓		Operating temperature (T-T)	0 - 40 °C
Surge energy rating	680 J	Storage temperature (T-T)	-15 - 45 °C
Output voltage Total Harmonic Distortion (THD)	5%	Operating relative humidity (H-H)	0 - 95%
Noise level	41 dB	Storage relative humidity (H-H)	0 - 95%
Surge protection ✓		Operating altitude	0 - 3000 m
Audible alarm(s) ✓		Non-operating altitude	0 - 15000 m
Audible alarm modes	Alarm when on battery, Low battery alarm, Overload alarm	Technical details	
Ports & interfaces		Sustainability certificates	ENERGY STAR, Green Premium
AC outlet types	C13 coupler	Compliance certificates	RoHS
Power plug	C14 coupler	Weight & dimensions	
AC outlets quantity	4 AC outlet(s)	Width	432 mm
Number of outlets (Battery backup & protection)	4	Depth	406 mm
USB port ✓		Height	86 mm
USB 2.0 ports quantity	1	Weight	20.5 kg
Serial interface ✓		Package width	535 mm
Serial interface type	RS-232	Package depth	570 mm
Ethernet LAN (RJ-45) ports	1	Package height	235 mm
SmartSlot ✓		Package weight	20.7 kg
Battery		Packaging data	
Battery technology	Sealed Lead Acid (VRLA)	Rack mount kit	✓
Number of batteries supported	1	Cables included	RJ-45, RS-232
Battery life (max)	6 year(s)	Resource CD	✓
		Software CD	✓
		Logistics data	
		Products per pallet	16 pc(s)
		Harmonized System (HS) code	85078000



0731304332930



731304332930

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.