Manhattan HDMI Cable with Ethernet, 4K@30Hz (High Speed), 3m, Male to Male, Black, Equivalent to HDMM3MHS, Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

Brand : Manhattan

Product code: 323222

Product name : HDMI Cable with Ethernet, 4K@30Hz (High Speed), 3m, Male to Male, Black, Equivalent to HDMM3MHS, Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag

HDMI Cable with Ethernet, 4K, Male to Male, 3m, 4K@30Hz, HEC, ARC, 3D, Shielded, Black, Polybag

Manhattan HDMI Cable with Ethernet, 4K@30Hz (High Speed), 3m, Male to Male, Black, Equivalent to HDMM3MHS, Ultra HD 4k x 2k, Fully Shielded, Gold Plated Contacts, Lifetime Warranty, Polybag:

High Speed Cables deliver high-definition performance._x000D_

HDMI has become the standard digital connection, delivering the highest-quality audio and video signal over a single cable. Manhattan High Speed HDMI Cables are designed and carefully constructed to meet the evolving needs of the high-definition marketplace. Manhattan High Speed HDMI Cables provide the highest resolution possible at 4K x 2K, an audio return channel and a bandwidth of 10.2 Gbps at 340 MHz. These high-quality cables provide high-definition video and multichannel, digital audio with increased performance characteristics, greater accuracy and expanded features, including Internet connectivity for home entertainment devices using a single HDMI connection.






Features

Cable length *	
Connector 1 *	
Connector 2 *	
Connector 1 gender *	
Connector 2 gender *	
Connector 1 form factor	
Connector 2 form factor	
Product colour *	
3D	
Supported graphics resolutions	
Audio Return Channel (ARC)	
HDMI Ethernet channel	
Data transfer rate	

3 m HDMI Type A (Standard) HDMI Type A (Standard) Male Male Straight Straight Black 3840 x 2160 10.2 Gbit/s

Features	
Bandwidth	340 MHz
Maximum refresh rate	30 Hz
AWG wire size	30
Connector contacts plating *	Nickel
Cable jacket material	Polyvinyl chloride (PVC)
Magnetically shielded	4
Certification	ISO 9002
Quantity per pack *	1 pc(s)
Weight & dimensions	
Weight	230 g
Package type	Polybag
Other features	
Technical features	340MHz
Logistics data	
Harmonized System (HS) code	84733080





766623323222

0766623323222



7666233232224

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.