


## APC Smart-UPS 750VA uninterruptible power supply (UPS) Line-Interactive 0.75 kVA 500 W 4 AC outlet(s)

Brand : APC Product code: SMT750RMI2UNC

Product name: Smart-UPS 750VA










Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	0.75 kVA	Rack capacity	2U
Output power *	500 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	151 V	LED indicators	✓
Input operation voltage (max) * 302 V Input frequency * 50/60 Hz	50/60 Hz	Certification	CE, EAC, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Output operation voltage (min) Output operation voltage (max)	220 V 240 V	Operational conditions	
Output frequency	50/60 Hz	Operating temperature (T-T)	0 - 40 °C
Output frequency regulation	+/- 3 Hz	Storage temperature (T-T)	-15 - 45 °C
Output requericy regulation  Output voltage regulation	5%	Operating relative humidity (H-H)	0 - 95%
Surge energy rating	459	Storage relative humidity (H-H)	0 - 95%
Response time	2 ms	Operating altitude	0 - 3000 m
Emergency Power Off (EPO)	0	Non-operating altitude	0 - 15000 m
Noise level	46 dB	. 5	0 13000 m
Surge protection	<b>√</b>	Technical details	
Audible alarm(s)	,	Sustainability certificates	Green Premium
Web-based management	1	Compliance certificates	RoHS
Audible alarm modes	Battery replacement	Weight & dimensions	
Auto-restart	<b>√</b>	Width	432 mm
Ports & interfaces		Depth	406 mm
	C12 coupler C14 coupler	Height	89 mm
AC outlet types	C13 coupler, C14 coupler	Weight	17.2 kg
Power plug	C14 coupler	Package width	546 mm
AC outlets quantity	4 AC outlet(s) 1	Package depth	584 mm
USB 2.0 ports quantity	1	Package height	241 mm
Ethernet LAN (RJ-45) ports	1	Package weight	21.2 kg
Battery		Packaging data	
,	Sealed Lead Acid (VRLA)	Rack mount kit	1
Battery capacity	168 Ah	Cables included	Input power cable, USB cable
Battery recharge time	3 h	Quick installation guide	<b>✓</b>
Hot-swap battery	<b>√</b>	Resource CD	<b>4</b>
Automatic battery test	<b>√</b>	Logistics data	
Cold start	✓		16 ng/g)
		Products per pallet	16 pc(s) 85078000
		Harmonized System (HS) code	0.00000

Other features	
Output voltage	230 V





731304327721

0731304327721

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.