

BenQ MH733 data projector Standard throw projector 4000 ANSI lumens DLP 1080p (1920x1080) White

Brand : BenQ

Product code: 9H.JGT77.1HE

Product name : MH733

- 4000 ANSI Lumens High Brightness

- Full HD 1080p Resolution

- USB Reader for PC-Less Presentations & Networked Presentation

DLP, 4000 Lum, 1920 x 1080, 16:9, 30-300", 2x HDMI, 2x VGA, LAN, RS-232, USB, 296x120x221 mm BenQ MH733. Projector brightness: 4000 ANSI lumens, Projection technology: DLP, Projector native resolution: 1080p (1920x1080). Light source type: Lamp, Service life of light source: 4000 h, Service life of light source (economic mode): 8000 h. Focus: Manual, Focal length range: 16.88 - 21.88 mm, Aperture range (F-F): 2.59 - 2.87. Analog signal format system: NTSC, PAL, SECAM, Supported graphics resolutions: 640 x 480 (VGA), 1920 x 1080 (HD 1080), Supported video modes: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p. Serial interface type: RS-232, HDMI connector type: Full-size





| Projector | | Network | |
|---|--------------------------------------|-------------------------------------|---|
| Screen size compatibility * | 762 - 7620 mm (30 - 300") | Ethernet LAN (RJ-45) ports | 1 |
| Projector brightness * | 4000 ANSI lumens | Wi-Fi * | × |
| Projection technology * | DLP | Storage | |
| Projector native resolution * | 1080p (1920x1080) | Card reader integrated * | × |
| Contrast ratio (typical) * Native aspect ratio * | 16000:1 16:9 | Features | |
| Number of colours | 1.073 billion colours | Noise level (economic mode) | 29 dB |
| Horizontal scan range | 15 - 102 kHz | On Screen Display (OSD) | |
| Vertical scan range | 23 - 120 Hz | | Arabic, Bulgarian, Simplified Chinese, Traditional Chinese, |
| Keystone correction, horizontal | -20 - 20° -30 - 30° | | Croatian, Czech, Danish, German, |
| Keystone correction, vertical Matrix type | -30 - 30* DMD | On Screen Display (OSD) languages | Dutch, English, Spanish, Finnish, French, Greek, Hindi, Hungarian, |
| Light source | 5.15 | | Indonesian, Italian, Japanese, Korean, Norwegian, Polish, |
| Light source type * | Lamp | | Portuguese, Romanian, Russian, Swedish, Thai, Turkish, Vietnamese |
| Service life of light source * | 4000 h | Number of OSD languages | 30 |
| Service life of light source (economic mode) | 8000 h | Noise level * | 33 dB |
| Lamp power | 240 W | Multimedia | |
| Lamps quantity | 1 lamp(s) | Built-in speaker(s) * | 1 |
| Lens system | | RMS rated power | 10 W |
| Focus * | Manual | Number of built-in speakers | 1 |
| Focal length range | 16.88 - 21.88 mm | Design | |
| Aperture range (F-F) | 2.59 - 2.87 | Market positioning * | Business |
| Zoom capability | V | Product type * | Standard throw projector |
| Zoom type | Manual | Product colour * | White |
| Zoom ratio | 1.3:1 | Placement | Desktop, Ceiling |
| Throw ratio | 1.15 - 1.5 | Cable lock slot | 4 |
| Offset | 105% | Cable lock slot type | Kensington |
| Video | | Display | |
| Analog signal format system * | NTSC, PAL, SECAM | Built-in display * | × |
| Full HD * 3D * | × | Power | |
| | 640 x 480 (VGA), 1920 x 1080 (HD | Power source * | AC |
| Supported graphics resolutions | 1080) | Power consumption (typical) * | 320 W |
| Supported video modes | 480i, 480p, 576i, 576p, 720p, 1080i, | | 0.5 W |
| | 1080p | Power consumption (max) | 355 W |
| Ports & interfaces | | Power consumption (economy mode) | 240 W |
| HDMI connector type | Full-size | AC input voltage | 100 - 240 V |
| USB 2.0 ports quantity * | 2 | | |

| Ports & interfaces | | Power | |
|---|-----------------------|---|--|
| Serial interface type * | RS-232 | AC input frequency | 50 - 60 Hz |
| PC Audio in | ✓ 2 2 ★ ✓ | Operational conditions | |
| PC Audio out VGA (D-Sub) ports quantity * HDMI ports quantity * DVI port * Mobile High-Definition Link (MHL) AC (power) in | | Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions | 0 - 40 °C -20 - 60 °C 10 - 90% 10 - 90% |
| Network | | Width | 296 mm |
| Smart TV * Ethernet LAN * | × ✓ | Depth Height Weight * | 221 mm 120 mm 2.5 kg |
| | | Packaging content | |

Remote control included *

Harmonized System (HS) code

Batteries included

Cables included Manual

Logistics data

∢

✔ AC, VGA

∢

85286200

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.