



Manhattan USB-C to USB-A Cable, 1m, Male to Male, 10 Gbps (USB 3.2 Gen2 aka USB 3.1), 3A (fast charging), Equivalent to USB31AC1M, SuperSpeed+ USB, Black, Lifetime Warranty, Polybag

Brand : Manhattan

Product code: 353373

Product name : USB-C to USB-A Cable, 1m, Male to Male, 10 Gbps (USB 3.2 Gen2 aka USB 3.1), 3A (fast charging), Equivalent to USB31AC1M, SuperSpeed+ USB, Black, Lifetime Warranty, Polybag

- USB type-C male to type-A male
- Connects a USB 3.0 or 2.0 type-A device to a SuperSpeed+ type-C port
- Supports speeds of up to 10 Gbps
- Supports current of up to 3.0 A
- SuperSpeed USB for ultra-fast data transfer rates with zero data degradation
- Lifetime Warranty

USB-C to USB-A Cable, 1m, 10 Gbps (USB 3.2 Gen2), 3A, Male to Male, Black, Polybag

[Manhattan USB-C to USB-A Cable, 1m, Male to Male, 10 Gbps \(USB 3.2 Gen2 aka USB 3.1\), 3A \(fast charging\), Equivalent to USB31AC1M, SuperSpeed+ USB, Black, Lifetime Warranty, Polybag:](#)

Manhattan SuperSpeed USB Type-C Cables easily connect USB type-A peripherals and accessories with type-C device ports. Ideal for use with any USB type-A, plug-and-play devices. Manhattan SuperSpeed USB Type-C Cables support data transfer rates up to 10 Gbps on Windows and Mac systems for fast, reliable transmissions and current up to 3 amps. Nickel-plated contacts, shielding and fully moulded boots with strain relief help provide dependable connections, maximum conductivity and minimal data loss with reduced EMI interference.



| Features | | Features | |
|----------------------------|---------------------------|--------------------------------|----------------------------|
| Cable length * | 1 m | Cable jacket material | Polyvinyl chloride (PVC) |
| USB version * | USB 3.2 Gen 2 (3.1 Gen 2) | Maximum data transfer rate | 10000 Mbit/s |
| Connector 1 * | USB A | Product colour * | Black |
| Connector 2 * | USB C | Certification | CE, UL 2725, USB 3.2 Gen 2 |
| Connector 1 gender * | Male | Weight & dimensions | |
| Connector 2 gender * | Male | Weight | 60 g |
| Connector 1 form factor | Straight | Packaging data | |
| Connector 2 form factor | Straight | Quantity per pack * | 1 pc(s) |
| AWG wire size | 30 | Package type | Polybag |
| Connector contacts plating | Nickel | Logistics data | |
| Magnetically shielded | ✓ | Harmonized System (HS) code | 84733080 |



0766623353373



766623353373

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.