manhattan

Manhattan USB-A 4-Port Hub, 4x USB-A Ports, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), Bus Power, Equivalent to ST4300MINU3B, Fast charging x1 Port up to 0.9A or x4 Ports with power jack (not included), SuperSpeed USB, Black, Three Year Warranty, Blister

Brand : Manhattan

Product code: 162296

Product name : USB-A 4-Port Hub, 4x USB-A Ports, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), Bus Power, Equivalent to ST4300MINU3B, Fast charging x1 Port up to 0.9A or x4 Ports with power jack (not included), SuperSpeed USB, Black, Three Year Warranty, Blister

USB 3.0 Hub, 4x USB 3.0 Ports, Bus Power, Fast charging x1 Port up to 0.9A or x4 Ports with power jack (not included), Black, Blister

Manhattan USB-A 4-Port Hub, 4x USB-A Ports, 5 Gbps (USB 3.2 Gen1 aka USB 3.0), Bus Power, Equivalent to ST4300MINU3B, Fast charging x1 Port up to 0.9A or x4 Ports with power jack (not included), SuperSpeed USB, Black, Three Year Warranty, Blister:

Powerful, fast SuperSpeed USB 3.0 performance in a multiport hub._x000D_
The Manhattan SuperSpeed USB 3.0 Hub easily expands USB access for desktop and mobile use to connect more peripherals and mobile devices. Create more connections for SuperSpeed USB 3.0 devices, such as storage devices and Web cameras. It's backward compatible to previous USB standards, providing versatility for attached devices. Plug and play with hot-swap capabilities, Windows and Mac compatibility and data transfer speeds up to 5 Gbps help the Manhattan SuperSpeed USB 3.0 Hub consolidate numerous, less-capable hubs into a single USB solution.

Ports & interfaces

Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
Hub interfaces *	USB 3.2 Gen 1 (3.1 Gen 1) Type-A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	4
Ports quantity *	4
DC-in jack	✔

Features

Data transfer rate *	5000 Mbit/s
Product colour	Black
Housing material	Plastic
LED indicators	✔
Plug and Play	✔
Certification	FCC, CE, RoHS, WEEE

Power

Power supply type	AC
Input voltage	100 - 240 V
Input current	0.6 A
AC input frequency	50 - 60 Hz

Power

Output voltage	5 V
Output current	3 A

System requirements

Windows operating systems supported	✔
Mac operating systems supported	Mac OS 9.0, Mac OS 9.1, Mac OS 9.2, Mac OS X 10.0 Cheetah, Mac OS X 10.1 Puma, Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks

Weight & dimensions

Width	45 mm
Depth	55 mm
Height	20 mm
Weight	60 g

Packaging data

Quantity per pack	1 pc(s)
Package type	Blister

Packaging content

Manual	✔

Logistics data

Harmonized System (HS) code	84719000

||||||| || |||| |||| ||| |||| ||| ||| ||||| || |||| ||| ||| |||| ||

0766623162296

766623162296