

ZYXEL

Zyxel NR7101 Cellular network router

Brand : Zyxel

Product code: NR7101-GB01V1F

Product name : NR7101

- 4G LTE
- 4x4 MIMO high-gain antennas
- 802.3af/at Gigabit PoE
- IP68 Ingress Protection
- Zyxel mobile apps

802.11 b/g/n, 2.4 GHz, 1G RJ-45, SIM, PoE, 255 x 256 x 58 mm, 1143 g, 280 x 420 x 108 mm, 2818 g, GB

Zyxel NR7101. Device type: Cellular network router, Product colour: White, Mounting: Wall mounting.

Ethernet LAN interface type: Gigabit Ethernet, Networking standards: IEEE 802.3af, IEEE 802.3at. Wi-Fi

standards: 802.11b, 802.11g, Wi-Fi 4 (802.11n), WLAN data transfer rates supported: 300 Mbit/s, Wi-Fi

frequency: 2.4 GHz. Data network: 4G, 5G, LTE, 4G standard: LTE-TDD & LTE-FDD. Security algorithms:

SSH, VPN support: Virtual Private Network (VPN) pass-through



Design		Performance	
Device type *	Cellular network router	Mobile operating systems supported	Android, iOS
Product colour *	White	Certification	CE, WEEE, RoHS, HSF
Mounting	Wall mounting	Management features	
Suitable for outdoor use	✓	Web-based management	✓
Reset button	✓	Management protocols	APN, PIN/PUK, MQTT
LED indicators	✓	Antenna	
Ethernet LAN features		Antenna type	Internal
Ethernet LAN *	✓	Antennas quantity	6
Ethernet LAN interface type	Gigabit Ethernet	Antenna gain level (max)	10 dBi
Networking standards	IEEE 802.3af, IEEE 802.3at	Power	
DHCP server	✓	Power source type *	PoE
Wireless LAN features		Power consumption (typical)	16 W
Wi-Fi *	✓	Operational conditions	
Wi-Fi standards	802.11b, 802.11g, Wi-Fi 4 (802.11n)	Operating temperature (T-T)	-40 - 60 °C
WLAN data transfer rates supported	300 Mbit/s	Storage temperature (T-T)	-40 - 65 °C
Wi-Fi frequency	2.4 GHz	Operating relative humidity (H-H)	5 - 95%
Mobile network		Storage relative humidity (H-H)	5 - 95%
Data network *	4G, 5G, LTE	Weight & dimensions	
4G standard	LTE-TDD & LTE-FDD	Width	255 mm
Number of SIM cards	2	Depth	256 mm
Ports & interfaces		Height	58 mm
Ethernet LAN (RJ-45) ports	1	Weight	1.14 kg
USB port	✗	Packaging data	
Security		Cables included	LAN (RJ-45)
Security algorithms	SSH	Package width	280 mm
Firewall	✓	Package depth	420 mm
IP address filtering	✓	Package height	108 mm
URL filtering	✓	Package weight	2.82 kg
DMZ support	✓		
Port forwarding	✓		

Security

VPN support

Virtual Private Network (VPN) pass-through

Logistics data

Harmonized System (HS) code

85176990



4718937619146

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-JUL-2024. Prints or copies of Information are only valid on the printed Publication date