Canon

Canon PIXMA TS7450a Inkjet A4 4800 x 1200 DPI Wi-Fi

Brand : Canon

Product family: PIXMA

Product code: 4460C058

Product name : TS7450a

Wireless Colour All in One Inkjet Photo Printer, Black

Canon PIXMA TS7450a Inkjet A4 4800 x 1200 DPI Wi-Fi:

The Canon PIXMA TS7450a is the perfect fit for versatile home use and effective home working: print, scan and copy from any device. It's so easy to connect and operate using the Canon PRINT app: this allin-one home printer offers mobile printing at its best. Stylish, affordable and simple to use, the PIXMA TS7450a offers the ability to print on many kinds of media from your computer, tablet or smartphone: print on photo paper, iron-on transfers, magnetic paper or restickable paper. With ADF technology, you can scan and copy multiple sheets in double-quick time, making home working faster and simpler. When work is over, the PIXMA TS7450a is as inventive as you are; it's ideal for artistic endeavours with children, or even for the big kid in you.

| Printing | | Paper handling | |
|---|---|------------------------------------|---|
| Duplex printing mode | Auto | Custom media width | 55 - 215.9 mm |
| Print technology * | Inkjet | Custom media length | 89 - 676 mm |
| Printing * | Colour printing | Paper tray media weight | 64 - 105 g/m² |
| Duplex printing * Maximum resolution * Print speed (ISO/IEC 24734) mono | 4800 x 1200 DPI 13 ipm | Ports & interfaces | |
| | | Direct printing * | 1 |
| Print speed (ISO/IEC 24734) colour | 6.8 ipm | USB port | 1 |
| Borderless printing | | USB connector | USB Type-B |
| 1 5 | • | Network | |
| Copying | Colour consist | Wi-Fi * | ✓ |
| Copying * | Colour copying | Ethernet LAN * | × |
| Maximum number of copies | 99 copies 25 - 400% | Wi-Fi standards | 802.11b, 802.11g, Wi-Fi 4 (802.11n) |
| Copier resize N-in-1 copy function | 25 - 400% | Security algorithms | WEP, WPA-PSK, WPA2-PSK |
| N-in-1 copy function (N=) | 2 | Mobile printing technologies | Apple AirPrint, Mopria Print Service, PIXMA Cloud Link |
| Scanning | | Design | |
| Scanning * | Colour scanning | Product colour * | Black |
| Optical scanning resolution * | 1200 x 2400 DPI | Market positioning * | Home & office |
| Scanner type * | Flatbed & ADF scanner | Built-in display * | 1 |
| Scan technology | CIS | Display | OLED |
| Input colour depth | 16 bit | Display diagonal | 3.66 cm (1.44") |
| Output colour depth Input greyscale depth | 8 bit 16 bit | Power | |
| Output greyscale depth | 8 bit | Power consumption (copying) | 14 W |
| | 0 bit | Power consumption (off) | 0.3 W |
| Fax | | AC input voltage | 100 - 240 V |
| Faxing * | × | AC input frequency | 50 - 60 Hz |
| Features | | System requirements | |
| Duplex functions * | Print | Windows operating systems | Windows 10, Windows 7, Windows 8.1 |
| Number of print cartridges * | 2 | supported | |
| Input & output capacity | | | Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 |
| Total number of input trays * | 1 | | Mojave, Mac OS X 10.15 Catalina, |
| Total input capacity * | 100 sheets | | Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 |
| Auto document feeder (ADF) | 1 | Mac operating systems supported | anther, Mac OS X 10.3 Tiger, Mac |
| Auto document feeder (ADF) input capacity | 35 sheets | OS X 10 Snow Le | OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, |
| Paper handling | | | Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 |
| Maximum ISO A-series paper size * | A4 | | Big Sur |
| Paper tray media types * | Envelopes, Photo paper, Plain paper | Mobile operating systems supported | |
| | | Other operating systems supported | ChromeOS |



Paper handling

| ISO A-series sizes (A0A9) * | | | |
|-----------------------------|--|--|--|
| ISO B-series sizes (B0B9) | | | |
| Non-ISO print media sizes | | | |
| Envelopes sizes | | | |
| Photo paper sizes | | | |
| | | | |

Borderless printing media sizes

A4, A5 Β5 Letter Com-10, DL 10x15,13x18,13x13,20x25 10x15, 13x18, 13x13, 20x25, A4, B5, Letter

Operational conditions

| Operating relative humidity (H-H) Storage temperature (T-T) | 10 - 80% 15 - 30 °C |
|--|------------------------|
| Weight & dimensions | |
| Width | 403 mm |
| Depth | 364 mm |
| Height | 206 mm |
| Weight | 8.2 kg |
| Packaging content | |
| Cartridge(s) included | √ |
| Cables included | AC |
| Logistics data | |
| Harmonized System (HS) code | 84433100 |



4549292198607

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.