

## Lindy 5m USB 3.2 Type A to B Cable, Anthra Line

Brand: Lindy Product code: 36744

Product name: 5m USB 3.2 Type A to B Cable, Anthra

Line

- Professional choice USB 3.0 Type A to B cable for commercial and high performance AV and IT installations
- Supports SuperSpeed data transfer speeds up to 5Gbps
- Robust PVC housing, gold plated connectors and contacts
- Double shielded cable, corrosion resistant tinned copper conductors
- SuperSpeed, USB 3.0, 5Gbps; 10 year warranty


5m USB 3.2 Typ A to B Cable, 5Gbps, Anthra Line

Lindy 5m USB 3.2 Type A to B Cable, Anthra Line. Cable length: 5 m, Connector 1: USB A, Connector 2: USB B, USB version: USB 3.2 Gen 1 (3.1 Gen 1), Maximum data transfer rate: 5000 Mbit/s, Connector contacts plating: Gold, Product colour: Black





Features		Features	
Cable length * USB version * Connector 1 * Connector 2 * Connector 1 gender * Connector 2 gender * Connector 1 form factor Connector 2 form factor	e length * 5 m  version * USB 3.2 Gen 1 (3.1 Gen 1)  version * USB A  vector 1 * USB B  vector 2 gender * Male  vector 2 gender * Male  vector 1 form factor Straight  vector 2 form factor Straight  vector 2 form factor Gold  vector 3 form factor Straight  vector 4 form factor Straight  vector 5 form factor Straight  vector 6 form factor Straight  vector 7 form factor Straight  vector 8 fold  vector 6 fold  vector 6 fold  vector contacts plating Folyvinyl chloride (PVC)  vector 8 fielding  vector 8 fielding  vector 8 field material  vector 9 folyvinyl chloride (PVC)  vector 8 field material  vector 9 folyvinyl chloride (PVC)	Product colour * Cable type Nominal attenuation Certification  Weight & dimensions  Cable diameter Bend radius (min)	Black Round cable 0.5-5m: 0.5MHz-7.5GHz25DB RoHS, REACH, UL  5.5 mm 4.8 cm
AWG wire size Connector material Contact material		Connector 1 dimensions (WxDxH) Connector 2 dimensions (WxDxH) Packaging data	12 x 4.5 x 36 mm 6.6 x 7.3 x 34.4 mm
Connector contacts plating Cable jacket material Conductor material		Quantity per pack * Package type  Operational conditions	1 pc(s) Polybag
Connector shielding Connector shield material Connector housing material Maximum data transfer rate		Operating temperature (T-T) Storage temperature (T-T) Technical details	0 - 60 °C 0 - 60 °C
		Harmonized System (HS) code	84733080



4002888367448

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.